


Contents

Page

1 .	Pipe material	1
2 .	Axles	2
3 .	Load capacity diagram	3
4 .	Description accumulation/friction rollers	4
5 .	Gravity conveyor rollers	6-33
6 .	Stub roller	35
7 .	Conveyor belt drums	36
8 .	Powered conveyor rollers with belt grooves	37-38
9 .	Powered conveyor rollers with tooth belt drive	39-40
10 .	Tooth belts and motor drive wheels	41
11 .	Powered accumulation conveyor rollers with flat belt drive	42
12 .	Powered conveyor rollers with multi-ribbed belt wheel	43
13 .	Powered conveyor rollers with single chain wheel	44-59
14 .	Powered conveyor rollers with adjustable friction	48-49 / 65-66
15 .	Centre distance	60
16 .	Powered conveyor rollers with double chain wheel	62-70
17 .	Conical conveyor rollers	71
18 .	Conical gravity conveyor rollers	72
19 .	Conical conveyor rollers with single chain wheel	73
20 .	Conical conveyor rollers with double chain wheel	74
21 .	Conical conveyor rollers with multi-ribbed belt wheel	76
22 .	Conical conveyor roller with belt grooves	77
23 .	Conical conveyor roller with round belt drive	78
24 .	Guide discs, buffer rings, back up rings	79
25 .	Push-on caps	80
26 .	Mini roller	82
27 .	Conveyor wheels	83
28 .	Roller strips	84-86
29 .	Roller tracks	87-92
30 .	Brake rollers	93-94
31 .	Clutch brake system KB1512	95-96
32 .	Roller dimensions	97-106
33 .	PEKO inquiry form	108
34 .	Terms of sale and delivery	

Pipe material



Order reference	Material
S	Steel pipe EN 10305-3
SV	Steel pipe galvanised
SG	Steel pipe rubberised
SP	Steel pipe with PVC-Coating (PVC 65° Shore silver grey)
N	Stainless Steel pipe (Niro) W No.1.4301
PG	Plastic pipe PVC gray RAL 7011
PB	Plastic pipe PVC blue RAL 5010
ALU	Aluminium pipe AlMgSi 0.5

Pipe-Ø RD	Wall thickness WS	Pipe weight in kg/m							
		S	SV	SG	SP	N	PG	PB	ALU
16,0	1,0	0,370	0,370	○		0,370			
20,0	1,5	0,684	0,684	○		0,684		0,137	0,235
30,0	1,0	0,715	0,715	○	●	0,715			
	1,5	1,054	1,054	○	●				
	1,8						0,245	0,245	
32,0	2,0	1,480	1,480	○	●	1,480			
40,0	1,5	1,425	1,425	○	●	1,425	0,419		
	2,3								
	3,0	2,737	2,737	○	●				
48,0	1,5	1,720	1,720	○					
	2,0	2,269	2,269	○					
50,0	1,5	1,794	1,794	○	●	1,794			0,617
	2,0	2,368	2,368	○	●	2,368			
	2,8						0,640	0,640	
	3,0	3,477	3,477	○	●				
60,0	1,5	2,164	2,164	○	●				
	2,0	2,861	2,861	○	●				
	3,0	4,217	4,217	○	●				
60,3	1,65				●	2,385			
63,0	3,0						0,870		
63,5	2,9	4,334	4,334	○	●				
70,0	2,0	3,354	3,354	○					1,154
80,0	2,0	3,847	3,847	○	●	3,847			
	3,0	5,696	5,696	○	●				
88,9	2,9	6,151	6,151			6,151			
108,0	3,6	9,272	9,272	○		9,272			
133,0	4,0	12,730	12,730	○					
159,0	4,5	17,153	17,153	○					


- hardened and/or polished designs upon request
- weight of coated pipe is dependent on the coating
- chromium-plated, nickel-plated or black-finished designs upon request
- designs with sound-absorbing inserts upon request


○ -Design upon request
● -In the standard

Other designs upon request.

Ordering
example

30x1,8 PG (Pipe Ø30, Wall thickness 1.8mm material PVC gray)
50x1,5 N (Pipe Ø50, Wall thickness 1.5mm material Niro)




Axle-Ø AD	Axle Weight in kg/m	Axle design AA					
		 Internal thread IG	 Spanner flat S	 Spring axle	 Smooth G	 External thread AG	 Deposited external thread BG
6	0,222			8	8	6x15	
8	0,395			10	10	8x15	
10	0,617	6x12	8x10	10	10	10x15	8x15
SK11	0,823			10	10		
12	0,888	8x15	10x10	10	10	12x15	10x15
14	1,208	8x15 10x15	12x10	10	10	14x20	10x15 12x15
15	1,387	8x15 10x15	12x10				14x20
17	1,782	10x15 12x20	14x10				16x20 14x20
20	2,466	10x15 12x20	14/15x10 14/15x13			20x25	16x20
25	3,853	16x24	18x10/13				20x25

- all threads metric
- all axles available in uncoated (A), galvanised (AV) or Niro (AN) W No.1.4305
- with outside thread AG is supplied with 1 nut on each side. Nuts M6/M8 DIN 934 and nuts M10/M12/M14/M16/M20 DIN 439B.

Other designs upon request.


Ordering example	A12 AG12x15 (Axle Ø12 uncoated with outside thread M12x15) AV12 IG8x15 (Axle Ø12 galvanised with inside thread M8x15) AN12 F (Spring axle Ø12 Niro)
---------------------	---

Load capacity diagram




Static load of the axles

with fixed clamping




with looser clamping




Static area load of the pipes


Steel pipe



Plastic pipe



Other dimensions upon request.



Function:


The drive element is continually powered via chains, tooth belts, flat belts or other types of drives. An anti-friction bushing is located between the drive element and the roller and there is thus no fixed connection between the drive and roller. The continual drive is transferred via the friction within the anti-friction bushing onto the roller. The drive force is dependent on the goods to be conveyed and the associated weight. If the goods being conveyed are stopped during an accumulation operation, the roller stops with good placement of the goods being conveyed although the drive element continues to turn. Friction between the drive element and the anti-friction bushing results which passes a certain dynamic pressure to the goods being conveyed. The material used by the drive element and anti-friction bushing such as plastic, steel, lubrication, etc. plays a major role. With an increasing accumulation length, the dynamic pressure can accumulate.


Drive force:

The drive force is dependent on various factors such as, for example, composition of the ground and weight of the goods being conveyed, location of the contact points of the conveyed goods to the rollers, conveying speed, temperature, lubrication, humidity, ratio of the accumulation operation to the entire operation time, etc.


Conveying speed:

The allowed conveying speed is from 0.15 to 0.5m/sec.







ST-001 / ST-001N



Conveyor roller bearings of thermoplastic material with row of balls. The balls are available in steel (ST-001) or Niro W no. 1.4034 (ST-001N).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	001	001N										
16x1	6	●	●	○		●				6	6										14
20x1,5	6,8	●	●	○		●	●	●	●	10	10										16
30x1	6,8,10	●	●	○	●	●				14	14										16
30x1,5	6,8,10	●	●	○	●	●				14	14										16
30x1,8	6,8,10						●	●		14	14										16
40x1,5	6,8,10	●	●	○	●	●				14	14										16
40x2,3	6,8,10						●	●		14	14										16

										
	Pipe-Ø	Axle-Ø	EL=	IG Internal thread	S Spanner flat	F Spring axle	G Smooth	AG External thread	BG Deposited external thread	
	16x1	6	RL+			3	3	13		
		6	RL+			5	5	15		
		8	RL+			5	5	18		
		10	RL+	6	5	5	5	15	5	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-001N-20x1,5N A8F EL=372



ST-003 / ST-003N



Conveyor roller bearings made of thermoplastic material with two rows of balls. The balls are available in steel (ST-003) or in stainless steel W-Nr 1.4034 (ST-003N). Stub axle of plastic, spring-loaded.



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	003	003N										
20x1,5	6	●	●			●	●	●	●	8	8										16
30x1,8	8						●	●		10	10										16
40x2,3	8,10						●	●		10	10										16
50x2,8	8,10						●	●		20	20										16

Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
	6	RL+			6			
	8	RL+			6			


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering example


ST-003N-20x1,5PB A6FF EL=372





ST-005



Conveyor roller bearings of thermoplastic material with grooved ball bearing 608 ZZ (ST-005). The ball bearing is available for wet operation also as RS (ST-005RS) or INOX (ST-005RSN).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	005											
30x1	8,10	●	●	○	●	●				60											
30x1,8	8,10						●	●		60											
32x2	8,10	●	●	○	●	●				60											

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		8	RL+					14		6
		10	RL+	10						


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering
example


ST-005-30x1SV A8 AG8x10, EL=372




ST-007



Friction bearings of thermoplastic material.



Pipe-Ø	Axle-Ø	Pipe design								007	Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU											
30x1	12	●	●	○	●	●				20										6
50x1,5	8,10,12,14	●	●	○	●	●			●	20										8
50x2,8	8,10,12,14						●	●		20										8
60x1,5	8,10,12,14	●	●	○	●					20										10
60x2	8,10,12,14	●	●	○	●					20										10
60,3x1,65	8,10,12,14					●				20										10
63x3	8,10,12,14						●	●		20										10

Pipe-Ø	Axle-Ø	EL=	     					
			IG	S	F	G	AG	BG
	8	RL+			7	7	21	
	10	RL+	10	7	7	7	18	10
	12	RL+	10	7	7	7	20	10
	14	RL+	10	7	7	7	22	10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-007-30x1SV A12 IG8x12 EL=372



ST-009 / ST-009N



Conveyor roller bearings of thermoplastic material with two rows of balls. The balls are available in steel (ST-009) or in Niro W no. 1.4034 (ST-009N).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	600	N600										
50x1,5	8,10,SK11,12	●	●	○	●	●			●	30	30										7
50x2,8	8,10,SK11,12						●	●		30	30										7
60x1,5	8,10,SK11,12	●	●	○	●					30	30										10
60,3x1,65	8,10,SK11,12					●				30	30										10
63x3	8,10,SK11,12						●	●		30	30										10

Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	8	RL+			7	7	21	
	10	RL+	8	7	7	7	18	8
	SK11	RL+			7	7		
	12	RL+	8	7	7	7	20	8


*- To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

ST-009-50x1,5N AN8 F EL=372






ST-013



Conveyor roller bearings of galvanised sheet steel with cone ball bearings. Ball cage of plastic.



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	013											
30x1,5	8,10	●	●	○	●					60											2
40x1,5	8,10,SK11,12	●	●	○	●					160											2
48x1,5	8,10,SK11,12	●	●	○						160											2
50x1,5	8,10,SK11,12	●	●	○	●					160											2
50x2	8,10,SK11,12	●	●	○	●					160											2
60x1,5	8,10,SK11,12	●	●	○	●					160											2
60x2	10,SK11,12	●	●	○	●					160											2
80x2	10,SK11,12	●	●	○	●					160											2

Pipe-Ø	Axle-Ø	EL=	IG	S	F	G	AG	BG
	8	RL+	IG	S	F	G	AG	BG
	10	RL+	10	6	6	6	20	7
	SK11	RL+					17	
	12	RL+	10	6	6	6	19	7
80x2	10	RL+	12	12	12	12	22	12
	SK11	RL+						
	12	RL+	12	12	12	12	24	12


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-013-40x1,5SV ASK11 F EL=372




ST-017



Conveyor roller bearings of galvanised sheet cone ball bearings.



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	017											
50x1,5	10,SK11,12	●	●	○	●					240											3
50x2	10,SK11,12	●	●	○	●					240											3
50x3	10,SK11,12	●	●	○	●					240											3
60x1,5	10,SK11,12	●	●	○	●					240											3
60x2	10,SK11,12	●	●	○	●					240											3
80x2	10,SK11,12	●	●	○	●					240											3

Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	10	RL+	10	10	9	9	19	
	SK11	RL+			9	9		
	12	RL+	10	10	9	9	21	10
80x2	10	RL+	9	7	7	7	19	
	SK11	RL+			7	7		
	12	RL+	9	7	7	7	21	9


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-017-50x1,5SV A12 IG8x15 EL=372





ST-018



Conveyor roller bearings of galvanised sheet steel with cone ball bearings also for use in high or low temperatures.
+240°C / -40°C



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	80	10	12	14	15	18	20	22	24	26	28	30
50x1,5	10,SK11,12,14,15	●	●	○	●					240											3
50x2	10,SK11,12,14,15	●	●	○	●					240											3
60x1,5	10,SK11,12,14,15	●	●	○	●					240											3
60x2	10,SK11,12,14,15	●	●	○	●					240											3
80x2	10,SK11,12,14,15	●	●	○	●					240											3

Pipe-Ø	Axle-Ø	EL=	     					
			IG	S	F	G	AG	BG
	10	RL+	10	6	6	6	17	
	SK11	RL+			6	6		
	12	RL+	10	6	6	6	19	6
	14	RL+	10	6		6	21	6
	15	RL+	10	6		6		6
80x2	10	RL+	6	7	7	7	19	
	SK11	RL+			7	7		
	12	RL+	6	7	7	7	21	9
	14	RL+	6	7		7	23	9
	15	RL+	6	7		7		9


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-018-50x1,5SV A15 BG12x10 EL=372






ST-021 / ST-021N



Conveyor roller bearings of thermoplastic material with labyrinth seal and cone ball bearings. The balls are available in steel /ST-021) or Niro W-no.1.4301 (ST-021N).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø21	N21N								
50x1,5	10,SK11,12,14,15	●	●	○	●	●			●	160	50								10
50x2	10,SK11,12,14,15	●	●	○	●	●				160	50								10
50x2,8	10,SK11,12,14,15						●	●		160	50								10
60x1,5	10,SK11,12,14,15	●	●	○	●					160	50								10
60x2	10,SK11,12,14,15	●	●	○	●					160	50								10
60,3x1,65	10,SK11,12,14,15					●				160	50								10
63x3	10,SK11,12,14,15						●	●		160	50								10
63,5x2,9	10,SK11,12,14,15	●	●	○						160	50								10
80x2	10,SK11,12,14,15	●	●	○	●	●				160	50								10

Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	10	RL+	7	6	6	6	17	7
	SK11	RL+			6	6		
	12	RL+	7	6	6	6	19	7
	14	RL+	7	6		6	21	7
	15	RL+	7	6		6		7


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard



Ordering
example

ST-021-63x3PG A12 AG12x15, EL=372





ST-024



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6202. The ball bearing is also available as ZZ (ST-024Z), as RS (ST-024RS) or INOX (ST-024RSN).

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	024									
40x1,5	8,10,SK11,12,14,15	●	●	○	●	●				220									8

Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
	8	RL+			11	11	23	
	10	RL+	11	11	11	11	20	11
	SK11	RL+			11	11		
	12	RL+	11	11	11	11	22	11
	14	RL+	11	11	11	11	24	11
	15	RL+	11	11	11	11		11


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.*

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering example


ST-024-40x1,5 SV A10 F EL=372




ST-025



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6002 (ST-025) and labyrinth seal. The ball bearing is also available as 2RS (ST-025RS), INOX (ST-025RSN) or Delrin (ST-025D).



Pipe-Ø	Axle Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	025	025D								
40x1,5	8,10,SK11,12,14	●	●	○	●	●				160									13
50x1,5	8,10,SK11,12,14,15	●	●	○	●	●			●	160	40								10
50x2	8,10,SK11,12,14,15	●	●	○	●	●				160	40								10
50x2,8	8,10,SK11,12,14,15						●	●		160	40								10
60x1,5	8,10,SK11,12,14,15	●	●	○	●					160	40								10
60x2	8,10,SK11,12,14,15	●	●	○	●					160	40								10
60,3x1,65	8,10,SK11,12,14,15					●				160	40								10
63x3	8,10,SK11,12,14,15						●	●		160	40								10
63,5x2,9	8,10,SK11,12,14,15	●	●	○						160	40								10
80x2	10,SK11,12,14,15	●	●	○	●	●				160	40								10
88,9x2,9	10,SK11,12,14,15	●	●	○	●	●				160	40								10

Pipe-Ø	Axle-Ø	EL=	     						
			IG	S	F	G	AG	BG	
40x1.5		RL+	6	6	5	5	**	6	
60-63.5		RL+	6	6	6	6	***	6	
	8	RL+	6	6	5	5	19		
	10	RL+	6	6	5	5	16	6	
	SK11	RL+			5	5			
	12	RL+	6	6	5	5	18	6	
	14	RL+	6	6		5	20	6	
	15 Laby lose	RL+	6	6				6	

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

** A10=16 / A12=17 / A14=20

*** A8=19 / A10=16 / A12=18 / A14=20


Other designs upon request.

○ -Design upon request



● -In the standard

Ordering
example

ST-025-50x1,5 ALU AN12 IG8x15, EL=372



ST-026



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6002 (ST-025) and labyrinth seal. The ball bearing is also available as 2RS (ST-025RS), INOX (ST-025RSN) or Delrin (ST-025D).

Pipe-Ø	Axle Ø	Pipe design										Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø26											
50x1,5	8,10,SK11,12,14,15	●	●	○	●	●			●	160											10

Pipe-Ø	Axle-Ø	EL=								
			Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG		
	8	RL+	7	7	5	5	19			
	10	RL+	7	7	5	5	16	7		
	SK11	RL+			5	5				
	12	RL+	7	7	5	5	18	7		
	14	RL+	7	7		5	20	7		
	15 Laby lose	RL+	6	6				7		


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- -Design upon request
- -In the standard

Ordering example


ST-026-50x1,5 SV A12 IG8x15, EL=450



ST-028



Conveyor roller bearings of galvanised sheet steel with grooved ball bearing 6202/6003 (ST-028). The ball bearing is also available as ZZ (ST-028Z) or 2RS (ST-028RS).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per											
		S	SV	SG	SP	N	PG	PB	ALU	028											
50x2	10,SK11,12,14,15,17	●	●	○	●					240											2
60x2	10,SK11,12,14,15,17	●	●	○	●					240											3
63,5x2,9	10,SK11,12,14,15,17	●	●	○						240											3
70x2	10,SK11,12,14,15,17	●	●	○						240											3

Pipe-Ø	Axle-Ø	EL=	     						
			IG	S	F	G	AG	BG	
	10	RL+	16	15	15	15	25	16	
	SK11	RL+							
	12	RL+	16	15	15	15	27	16	
	14	RL+	16	15		15	29	16	
	15	RL+	16	15		15		16	
	17	RL+	16	15		15		16	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ -Design upon request
● -In the standard

Ordering
example


ST-028-70x2 SV A14 S10x10 EL=372






ST-029



Conveyor roller bearings of galvanised sheet steel with grooved ball bearing 6202/6003 (ST-029). The ball bearing is also available as ZZ (ST-029Z) or 2RS (ST-029RS).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	Ø											
50x1,5	10,SK11,12,14,15,17	●	●	○	●	●				240											3
50x2	10,SK11,12,14,15,17	●	●	○	●	●				240											3
60x1.5	10,SK11,12,14,15,17	●	●	○	●					240											4
60.3x1.65	10,SK11,12,14,15,17					●				240											4
60x2	10,SK11,12,14,15,17	●	●	○	●					240											4
60x3	10,SK11,12,14,15,17	●	●	○	●					240											4
63.5x2.9	10,SK11,12,14,15	●	●	○	●					240											4
70x2	10,SK11,12,14,15,17	●	●	○						240											4
80x2	10,SK11,12,14,15,17	●	●	○	●					240											3
80x3	10,SK11,12,14,15,17	●	●	○	●					240											3

Pipe-Ø	Axle-Ø	EL=	     						
			IG		F	G	AG	BG	
	10	RL+	11	10	10	10	20	10	
	SK11	RL+			10	10			
	12	RL+	11	10	10	10	22	10	
	14	RL+	11	10		10	22	10	
	15	RL+	11	10		0		10	
	17	RL+	11	10		0		10	
80	12,14	RL+	9	9	7	7		9	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering
example


ST-029-60x2 SV A15 S12x15, EL=372




ST-030



Conveyor roller bearings of galvanised sheet steel with grooved ball bearing 6202/6003 (ST-030). The ball bearing is also available as ZZ (ST-030Z) or 2RS (ST-030RS).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø									
50x1,5	15,17	●	●	○	●	●				240									3
50x2	15	●	●	○	●	●				240									3
60x1.5	15	●	●	○	●					240									4
60.3x1.65	15					●				240									4
60x2	15,17	●	●	○	●					240									4
60x3	15,17	●	●	○	●					240									4
70x2	15,17	●	●	○						240									4
80x2	15,17	●	●	○	●					240									4

Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	15	RL+	11	10	10	10		10
	17	RL+	11	10	10	10		10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- -Design upon request
- -In the standard

Ordering
example


ST-030-60x2 SV A15 F, EL=372



ST-031



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6004 ZZ (ST-031). The ball bearing is for wet operation and is also available as RS (ST-031RS) or INOX (ST-031RSN).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø31									
50x1,5	20	●	●	○	●	●				360									10
50x2	20	●	●	○	●	●				360									10
60x1,5	20	●	●	○	●	●				360									10
60x2	20	●	●	○	●	●				360									10

Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
20	20	RL+	10	10			26	10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering example


ST-031-50x2 S A20 S14x13, EL=372




ST-033



Conveyor roller bearings of uncoated or galvanised sheet steel with grooved ball bearing 6204/6004 with axle 20 or 6205/6005 with axle 25. The ball bearing is also available as ZZ (ST-033Z) or 2RS (ST-033RS).



Pipe-Ø	Axle-Ø	Pipe design									Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	033										
63,5x2,9	17	●	●	○						360										4
63,5x2,9	20	●	●	○						400										4
80x2	17,20,25	●	●	○	●	●				500										5
80x3	17,20,25	●	●	○	●					500										5
88,9x2,9	17,20,25	●	●	○	●	●				500										5
108x3,6	17,20,25	●	●	○						500										6

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		17	RL+	10	10				10	
		20	RL+	10	10			26	10	
		25	RL+	10	10				10	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.



○ - Design upon request
● - In the standard

Ordering
example

ST-033-88,9 x2,9 SV A20 IG12x18, EL=372




ST-034



Conveyor roller bearings of uncoated or galvanised sheet steel with grooved ball bearing 6004/6204 with axle 20 or 6205 with axle 25.
The ball bearing is also available as ZZ (ST-034Z) or 2RS (ST-034RS).

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	034											
63,5x2,9	20	●	●	○						400											4
80x2	SK14,17,20	●	●	○	●	●				500											5
80x3	SK14,17,20	●	●	○	●					500											5
88,9x2,9	SK14,17,20,25	●	●	○	●	●				500											5
108x3,6	SK14,17,20,25	●	●	○						500											6

Pipe-Ø	Axle- Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	SK14	RL+			10	10		
	17	RL+	11	11				11
	20	RL+	11	11			32	11
	25	RL+	11	11				11


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-034-88,9 x2,9 SV A20 IG12x18, EL=372





ST-037



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6204 (ST-037). The ball bearing is also available as ZZ (ST-037Z) or 2RS (ST-037RS).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	037									
60x2	17,20	●	●	○	●					360									10
63,5x2,9	17,20	●	●	○						360									10
80x2	17,20	●	●	○	●	●				360									10
88,8x2,9	17,20	●	●	○		●				360									10

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		17	RL+	12	11				12	
		20	RL+	7	6			27	7	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.



○ - Design upon request
● - In the standard

Ordering
example

ST-037-88,9 x2,9 SV A20 S 15x13 EL=372



ST-040



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6204ZZ (ST-040Z) and labyrinth seal. The ball bearing is also available as RS (ST-040RS) or INOX (ST-040RSN).

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø40									
88,9x2,9	20	●	●	○	●	●				300									16
108x3,6	20	●	●	○						300									16

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		20	RL+	10	10			26	10	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering example


ST-040-88,9 x2,9 SV A20 IG12x18, EL=372



ST-041



Conveyor roller bearings of thermoplastic material with grooved ball bearing 6004/6005 (ST-041). The ball bearing is also available as 2RS (ST-041RS) or INOX (ST-041RSN).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	104									
63.5x2.9	15,17,20,25	●	●	○	●	●				180									10

Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
15		RL+	10	10				10
17		RL+	10	10				10
20		RL+	10	10			26	10
25		RL+	10	10				10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.



- - Design upon request
- - In the standard

Ordering example

ST-041-63.5x2.9 SV A20 IG10x15, EL=385





ST-044



Conveyor roller bearings of uncoated or galvanised sheet steel with grooved ball bearing 6204 ZZ with axle 20 or 6005 ZZ with axle 25. With pipe diameter of 40 with ball bearing 6202 ZZ resp. 6003 ZZ. The ball bearing is also available as 2RS (ST-044RS).

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	Ø4											
40x1.5	8,10,SK11,12,14,15,17	●	●	○	●					120											3
63,5x2,9	17	●	●	○						360											5
63,5x2,9	20	●	●	○						500											5
80x2	17,20,25	●	●	○	●	●				560											5
80x3	17,20,25	●	●	○	●					560											5
88,9x2,9	20,25	●	●	○	●	●				560											5
108x3,6	20'25	●	●	○						560											6

Pipe-Ø	Axle-Ø	EL=	     					
			IG	S	F	G	AG	BG
40x1.5	8	RL+	11	11	11			
	10	RL+	11	11	11			
	SK11	RL+	11	11	11			
	12	RL+	11	11	11			
	14	RL+	11	11	11			
	15	RL+	11	11				
	17	RL+	11	11				
	17	RL+	10	10				10
	20	RL+	10	10			26	10
	25	RL+	10	10				10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- -Design upon request
- -In the standard

Ordering
example


ST-044-88,9 x2,9 SV A20 IG12x18, EL=372



ST-045



Conveyor roller bearings of uncoated sheet steel welded in the pipe with grooved ball bearing 6204 with axle 20 or 6305 with axle 25. The ball bearing is also available as 2RS (ST-045RS).



Pipe-Ø	Axle -Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	Ø45									
63,5x2,9	20	●	●	○						560									10
80x2	20	●	●	○	●					560									10
80x3	20	●	●	○	●					560									10
88,9x2,9	20,25	●	●	○	●					560									10
108x3,6	20,25	●	●	○						560									10
133x4	20,25	●	●	○						560									10

Pipe-Ø	Axle- Ø	EL=	Internal thread Spanner flat Spring axle Smooth External thread Deposited external thread					
			IG	S	F	G	AG	BG
63,5x2,9	20	RL+	10	10			30	10
	20	RL+	10	6			26	6
	25	RL+	10	6				6


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering
example


ST-045-133x4 SV A20 S14x13 EL=1400



ST-046



Conveyor roller bearings of uncoated sheet steel welded in pipe with grooved ball bearing 6204 ZZ with axle 20 or 6305 with axle 25. The ball bearing is also available as 2RS (ST-046RS). From axles 25, also available as NIRO stock. (ST-046N)



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	046									
63,5x2,9	20	●	●	○						560									10
80x2	20	●	●	○	●					560									10
80x3	20	●	●	○	●					560									10
88,9x2,9	20,25	●	●	○	●					560									10
108x3,6	20,25	●	●	○						560									10
133x4	20'25	●	●	○						560									10

Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
			IG	S	F	G	AG	BG
	20	RL+	6	6			24	6
	25	RL+	6	6				6


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-046-133x4 SV A20 S14x13 EL=2200




ST-047



Conveyor roller bearings of steel/Niro twisted, welded in the pipe with grooved ball bearing 6204/6004 ZZ with axle 20 or 6205/6005 ZZ with axle 25. The ball bearing is also available as 2RS (ST-047RS) or as 2RS-INOX (ST-047RSN).



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	047									
63,5x2,9	20,25	●	●	○						560									10
80x2	20,25	●	●	○	●	●				560									10
80x3	20,25	●	●	○	●					560									10
88,9x2,9	20,25	●	●	○	●	●				560									10
108x3,6	20,25	●	●	○						560									10
133x4	20,25	●	●	○						560									10

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		20	RL+	10	10			26	10	
		25	RL+	10	10				10	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


ST-047-133x4 SV A20 S14x13 EL=2200




ST-049



Bearing seat rotated directly in pipe with grooved ball bearing 6202/6003 ZZ or 6204/6303 ZZ and shaft locking clip.



Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	St 304									
40x3	15,17	●	●	○	●					360									0
50x2	17,20	●	●	○	●					360									0
50x3	17,20	●	●	○	●					360									0

										
	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		15	RL+	10	10				10	
		17	RL+	10	10				10	
		20	RL+	10	10			26	10	


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

ST-049-50x2 SV A20 S14x13 EL=1100






ST-025 / ST-045



	025	045
a =	25mm	30mm
b =	10mm	15mm
f =	3mm	0mm
RL min =	60mm	92mm
RL max =	150mm	150mm

The covers for the stub roller are pressed in and also available welded with type 045. With stub rollers, the mass of EL is always given as 0.
Please find information on bearing from the corresponding gravity conveyor roller.

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	025	045								
50x1,5	14	●	●	○	●	●			●	25									10
50x2	14	●	●	○	●	●				25									10
50x2,8	14						●	●		15									10
60x1,5	14	●	●	○	●					25									10
60x2	14	●	●	○	●					25									10
60,3x1,65	14					●				25									10
63x3	14						●	●		15									10
63,5x2,9	14,20	●	●	○						25	100								10
80x2	14,20	●	●	○	●	●				25	100								10
80x3	20	●	●	○	●						100								10
88,9x2,9	14,20	●	●	○	●	●				25	100								10
108x3,6	20	●	●	○							100								10
133x4	20	●	●	○							100								10

										
	Pipe-Ø	Axle-Ø	AL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
025		14	RL + a + b -					1		
045		20	RL + a + b -					8		


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.

- - Design upon request
- - In the standard


Ordering
example

ST-045-88,9x2,9 SV A20 AG20x30 RL=80
Stub roller




Drive and deflecting rollers are available in various designs such as steel, Niro-steel, polyurethane or fibre glass reinforced polyester. The pipe can be supplied in cylindrical, conically beveled or spherical form.

Drive roll type 055



RD max = 400mm
RL max = 2500mm
AL max = 3000mm


Deflection roll type 047



RD max = 400mm
RL max = 2500mm
AL max = 3000mm


Other designs upon request

○ - Design upon request
● - In the standard




Conveyor roller with internal thread (IG)

ATS




Conveyor roller with smooth axle (G) or spring axle (F)

ATS




Conveyor roller with width across flats (S)

ATS




Conveyor roller with external thread (AG)




ATS




Powered conveyor roller with belt grooves



Pipe-Ø	Axle-Ø	Pipe design								Belts-Ø	Minimum	Maximum		SD	Possible bearing
		S	SV	SG	SP	N	PG	PB	ALU			a	b	a+b	
30x1	8	●	●	○	●					4	30	30	60	22	005
40x1,5	8,10,SK11,12,14,15	●	●	○	●					4	30	30	90	32	024, 013
50x1,5	10,SK11,12,14,15	●	●	○	●					5	30	30	120	40	025, 013
50x1,5	10,SK11,12,14,15	●	●	○	●					6	30	30	120	38	025, 013
50x2,8	10,SK11,12,14,15						●	●		5	30	30	97	40	025
60x1,5	10,SK11,12,14,15	●	●	○	●					6	35	30	120	48	025, 013
60x2	10,SK11,12,14,15,20	●	●	○	●					6	35	30	120	48	025, 013
63x3	10,SK11,12,14,15						●	●		5	35	35	120	53	025
80x2	10,SK11,12,14,15,20	●	●	○	●					8	35	30	100	64	025, 037

Bearing	Pipe-Ø	Axle-Ø									
005		8	e =					10			
013		8	e =			4	4	11			
		10	e =	6	4	4	4	9.5			
		SK11	e =			4	4				
		12	e =	6	4	4	4	10.5			
024		8	e =			10.5	10.5	16.5			
		10	e =	10.5	10.5	10.5	10.5	15			
		SK11	e =			10.5	10.5				
		12	e =	10.5	10.5	10.5	10.5	16			
		14	e =	10.5	10.5		10.5	17			
		15	e =	10.5	10.5		10.5				
025		10	e =	8.5	8	8	8	13.5			
		SK11	e =			8	8				
		12	e =	8.5	8	8	8	14			
		14	e =	8.5	8		8	15.5			
		15	e =	8.5	8		8				
037		20	e =	8.5	8			18.5			

Round belt wheel
of Delrin




Other designs upon request.

- - Design upon request
- - In the standard


Ordering
example

ATS/025-50x2,8PG A12 S8x6 EL=372
- one-sided 2 grooves a=67, b=30, SD=40


Powered conveyor roller with tooth belt wheel



AT1ZR PC8z20,K,Stau / AT1ZR PC8z20,K,Fest



Tooth belt wheel 8 M z20 for 2 toothed belts with 12mm width of thermoplastic material as accumulation drive (Friction) or as fixed drive (fixed) with Press fit. grooved ball bearing 6202 also available as ZZ (AT1R PC8z20 Z,K), as 2RS (AT1R PC8z20 RS,K) or as INOX (AT1R PC8z20 RSN,K).



a = 10mm, b = 25,4mm, c = 4mm, D = 55mm

For information on accumulation drive, see Page 4.

Stau = Friction
Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	011	013	017	021	021N	025	028	
50x1,5	12,14	●	●	○	●	●			●	40	40	40	40	40	40		
50x2	12,14	●	●	○	●	●					40	40	40	40	40	40	
50x2,8	12,14						●	●		40			40	40	40		
60x1,5	12,14	●	●	○	●					40	40	40	40	40	40		
60x2	12,14	●	●	○	●	●					40	40	40	40	40	40	
60,3x1,65	12,14					●				40			40	40	40		
63x3	12,14						●	●		40			40	40	40		
63,5x2,9	12,14	●	●	○									40	40	40	40	
80x2	12,14	●	●	○	●	●					40	40	40	40	40		

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
011	●	●		12	RL+	44						9
013	●	●		12	RL+	43						6
017	●	●		12,14	RL+	45						7
021/021N	●	●		12,14	RL+	43						10
025	●	●		12,14	RL+	43						10
028	●	●		12,14	RL+	48						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


When using 8 M toothed belt wheels, a centre distance tolerance of +0/-0.3mm is to be maintained .

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example

AT1ZR PC8z20,K,Fest
025-50x1,5 SV A12 IG8x15, EL=432




AT2ZR PC8z20,verschweisst



Steel/Niro - Tooth belt wheel 8 M z20 for 2 tooth belts with 12mm width welded in pipe. Available as grooved ball bearing 6202 ZZ (AT2R PC8z20) or as 2RS (AT2R PC8z20 RS).

verschweisst = welded



a = 10mm, b = 12,5mm, c = 10mm, f = 1,2mm
D = 56mm, N = 35, e = 49,4

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	011	013	017	021	021N	025	028	
50x1,5	12,14	●	●	○	●	●				100	100	100	100	60	100		
50x2	12,14	●	●	○	●	●					100	100	100	60	100	100	
60x1,5	12,14	●	●	○	●					100	100	100	100	60	100		
60x2	12,14	●	●	○	●						100	100	100	60	100	100	
60,3x1,65	12,14					●				100	100	100	100	60	100		
63,5x2,9	12,14	●	●	○									100	60	100	100	
80x2	12,14	●	●	○	●	●					100	100	100	60	100		


Counter-bearing	Friction	Fixed	Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle Spring axle  Smooth G  External thread AG  Deposited external thread BG						
						IG	S	Spring axle	G	AG	BG	
011				12	RL+	54						9
013				12	RL+	53						6
017				12,14	RL+	55						7
021/021N				12,14	RL+	53						10
025				12,14	RL+	53						10
028				12,14	RL+	58						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.
When using 8 M toothed belt wheels, a centre distance tolerance of +0/-0.3mm is to be maintained.


Other designs upon request.

○ -Design upon request
● -In the standard


Ordering example	AT2ZR PC8z20,verschweisst 025-50x1,5 SV A12 IG8x15, EL=432
------------------	---



M2R PC8z20,S / M2R PC8z20,N / M2R PC8z20,ALU



b = 12,5mm, f = 1,2mm
L = 32,5mm, d = 10mm
D = 56mm



Motor drive wheel 8M z = 20 for 2 tooth belts with width up to 12mm of steel, Niro or aluminium pre-drilled.
The drive wheel on the motor as well as the first drive head of the roller powered by the motor drive wheel must not be made of plastic.

Tooth belts

Order reference	Pitch	Centre distance at z20*	Number of teeth	Effective	Width
ZRPCC-8M,288,b=11,2	8 mm	64 mm	36	288 mm	11,2 mm
ZRPCC-8M,352,b=11,2	8 mm	96 mm	44	352 mm	11,2 mm
ZRPCC-8M,416,b=11,2	8 mm	128 mm	52	416 mm	11,2 mm
ZRPCC-8M,456,b=11,2	8 mm	148 mm	57	456 mm	11,2 mm
ZRPCC-8M,480,b=11,2	8 mm	160 mm	60	480 mm	11,2 mm
ZRPCC-8M,544,b=11,2	8 mm	192 mm	68	544 mm	11,2 mm
ZRPCC-8M,608,b=11,2	8 mm	224 mm	76	608 mm	11,2 mm
ZRPCC-8M,640,b=11,2	8 mm	240 mm	80	640 mm	11,2 mm
ZRPCC-8M,720,b=12,0	8 mm	280 mm	90	720 mm	12,0 mm
ZRPC-8M,800,b=12,0	8 mm	320 mm	100	800 mm	12,0 mm
ZRPC-8M,896,b=12,0	8 mm	368 mm	112	896 mm	12,0 mm
ZRPC-8M,1000,b=12,0	8 mm	420 mm	125	1000 mm	12,0 mm


* Maximum allowed centre distance tolerance +0/-0.3mm.

Other designs upon request.


Ordering
example

M2R PC8z20,S
ZRPC-8M,352,b=11,2

Powered accumulation conveyor roller for flat belts




AT1FR,KS,Stau



Flat belts drive head as accumulation drive.
Grooved ball bearing 6202 also available as ZZ (AT1FR Z,KS,Stau), as 2RS (AT1FR RS,KS,Stau) or as INOX (AT1FR RS,KS,Stau).

For information on accumulation drive, see Page 4.

Stau = Friction



a min = 55mm

Pipe-Ø	Axle-Ø	Pipe design									Maximum load bearing capacity per roller*	
		S	SV	SG	SP	N	PG	PB	ALU	025		
50x1,5	12,14	●	●	○	●	●			●	40		
50x2	12,14	●	●	○	●	●				40		
50x2,8	12,14						●	●		40		
60x1,5	12,14	●	●	○	●					40		
60x2	12,14	●	●	○	●	●				40		
60,3x1,65	12,14					●				40		
63x3	12,14						●	●		40		

Counter-bearing	Friction Fixed		Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
025	●			12,14	RL+ a +	7						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard



Ordering example

AT1FR,KS,Stau
025-50x1,5 SV A12 IG8x15 EL=432 a=57

Powered conveyor roller with multi-ribbed belt wheel



AT1MRI,K,Fest



Multi-ribbed belt wheel for PJ belts of thermoplastic material as a fixed drive with press fit.

Grooved ball bearing 6202 ZZ, available as 2RS (AT1MRI,RS,K) or as INOX (AT1MRI,RSN,K).

a = 12mm, b = 18.72mm, D = 43mm

Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*						
		S	SV	SG	SP	N	PG	PB	ALU	011	013	017	021	021N	025	
50x1,5	12,14	●	●	○	●	●			●	40	40	40	40	40	40	
50x2	12,14	●	●	○	●	●					40	40	40	40	40	
50x2,8	12,14						●	●		40			40	40	40	
60x1,5	12,14	●	●	○	●					40	40	40	40	40	40	
60x2	12,14	●	●	○	●	●					40	40	40	40	40	
60,3x1,65	12,14					●				40			40	40	40	
63x3	12,14						●	●		40			40	40	40	
63,5x2,9	12,14	●	●	○									40	40	40	
80x2	12,14	●	●	○	●	●					40	40	40	40	40	

Counter-bearing	Friction	Fixed	Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
011		●		12	RL+	37						9
013		●		12	RL+	36						6
017		●		12,14	RL+	39						7
021/021N		●		12,14	RL+	36						10
025		●		12,14	RL+	36			34.5	34.5		10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

When using PJ belts, a centre distance tolerance of +2.0/-0mm is to be maintained.

Information on the centre distance, can be found on page 60.


Other designs upon request

○ - Design upon request
● - In the standard


Ordering
example

AT1MRI,K,Fest
025-50x1,5 SV A12 IG8x15, EL=432

Powered conveyor roller with single chain wheel




AT1K 3/8z10,S,Stau / AT1K 3/8z10,S,Fest



Steel chain wheel 3/8"x7/32" z10 with normal toothing as accumulation drive (Friction) or as fixed drive (Fixed) with press fit.

Grooved ball bearing 608 also available as ZZ or 2RS.

Chain wheel-side also available with IG spigot. As fixed drive not suited for stop and go.



a=12mm, b=12,5mm, T=30,82mm, N=21mm

For information on accumulation drive, see Page 4.

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	001	001N	005							
30x1	8	●	●	○	●	●				14	14	20							
30x1,8	8						●	●		14	14	20							
32x2	8	●	●	○	●	●				14	14	20							

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
001/001N	●	●	8	8	RL+					34		11
005			8	8	RL+					32		6

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 3/8z10,S,Fest
005-30x1 SV A8 AG8x15 EL=432


Powered conveyor roller with single chain wheel



AT1K 1/2z11,K,Stau / AT1K 1/2z11,K,Fest



Plastic chain wheel 1/2"x5/16" z11 with rack and pinion toothing as accumulation drive (Friction) or as fixed drive (Fixed) with press fit. Grooved ball bearing 6202 also available as ZZ or 2RS. Also available with normal toothing. Not suitable for stop and go as fixed drive.



a=12mm, b=15,5mm, T=45,07mm, N=30mm

For information on accumulation drive, see Page 4.

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029
50x1,5	10,12,14	●	●	○	●	●			●	24	24	40	40	40	40	40	40	40	40
50x2	10,12,14	●	●	○	●	●							40	40	40	40	40	40	40
50x2,8	10,12,14						●	●		24	24	40			40	40	40		
50x3	10,12,14	●	●	○	●									40			40		
60x1,5	10,12,14	●	●	○	●					24	24	40	40	40	40	40	40		40
60x2	10,12,14	●	●	○	●	●							40	40	40	40	40	40	40
60,3x1,65	10,12,14					●				24	24	40			40	40	40		40
63x3	10,12,14						●	●		24	24	40			40	40	40		
63,5x2,9	10,12,14	●	●	○											40	40	40	40	40
80x2	10,12,14	●	●	○	●	●							40	40	40	40	40		40

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
009/009N	●	●		10,12	RL+	33						8
011	●	●		10,12	RL+	33						9
013	●	●		10,12	RL+	31						6
017	●	●		10,12,14	RL+	34						7
021/021N	●	●		10,12,14	RL+	31						10
025	●	●		10,12,14	RL+	31						10
028	●	●		10,12,14	RL+	37						7
029		●		10,12,14	RL+	34						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 1/2z11,K,Fest
025-50x1,5 SV A12 IG8x15, EL=432

Powered conveyor roller with single chain wheel




AT1K 1/2z11,S,Stau / AT1K 1/2z11,S,Fest



Steel chain wheel 1/2"x5/16" z11 with rack and pinion gearing as accumulation drive (Friction) or als fixed drive (Fixed) with press fit. Grooved ball bearing 6202 also available as ZZ or 2RS.

Not suitable for stop and go as fixed drive.

For information on accumulation drive, see Page 4.



a=12mm, b=15,5mm, T=45,07mm, N=31,5mm

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029
50x1,5	10,12,14	●	●	○	●	●			●	24	24	100	100	100	100	60	100	100	100
50x2	10,12,14	●	●	○	●	●							100	100	100	60	100	100	100
50x2,8	10,12,14						●	●		24	24	100			100	60	100		
50x3	10,12,14	●	●	○	●									100			100		
60x1,5	10,12,14	●	●	○	●					24	24	100	100	100	100	60	100		100
60x2	10,12,14	●	●	○	●								100	100	100	60	100	100	100
60,3x1,65	10,12,14					●				24	24	100			100	60	100		100
63x3	10,12,14						●	●		24	24	100			100	60	100		
63,5x2,9	10,12,14	●	●	○											100	60	100	100	100
80x2	10,12,14	●	●	○	●	●							100	100	100	60	100		100

Counter-bearing			Pipe-Ø	Axle-Ø	EL=							
	Friction	Fixed				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
009/009N	●	●		10,12	RL+	33						8
011	●	●		10,12	RL+	33						9
013	●	●		10,12	RL+	31						6
017	●	●		10,12,14	RL+	34						7
021/021N	●	●		10,12,14	RL+	31						10
025	●	●		10,12,14	RL+	31						10
028	●	●		10,12,14	RL+	37						7
029		●		10,12,14	RL+	34						7


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request. Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example


AT1K 1/2z11,S,Fest
025-50x1,5 SV A12 IG8x15, EL=432



Adjustable friction roller



AT1K 1/2z11,S,Stau "E"



a = 12mm
b = 18mm
h = 29mm
N = 32mm
T = 45,07mm

Steel chain wheel 1/2"x5/16" z11 as accumulation drive with adjustable drive force. drive head with grooved ball bearing 6001 ZZ also available with 6001 2RS (AT1K 1/2z11,RS,Stau "E") and counterbearing 024E with 6002 ZZ also available with 6002 2RS (024RS). Axle has inside thread M8x15 on both sides.

By adjusting the nuts on the fine thread M12x1.25, the friction on the friction disc and thus the drive force is increased.

Maximum allowed conveying speed 0.5 m/sec.

Stau = Friction


Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	024									
50x1,5	12	●	●	○	●	●			●	60									
50x2	12	●	●	○	●	●				60									
50x2,8	12						●	●		60									
60x1,5	12	●	●	○	●					60									
60x2	12	●	●	○	●					60									
60,3x1,65	12					●				60									
63x3	12						●	●		60									

Counter-bearing	Pipe-Ø	Axle-Ø	EL =	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
024E		12	RL +	59						10


Ordering example

AT1K 1/2z11,Stau "E"
024E-50x1,5 SV A12 IG8x15 EL=567

Adjustable friction roller



AT1K 1/2z11,S,Stau "EK"



a = 12mm
 b = 15,5mm
 f = 2mm
 h = 29mm
 N = 31,5mm
 T = 45,07mm

Steel chain wheel 1/2"x5/16" z11 as accumulation drive with adjustable drive force. Drive head with grooved ball bearing 6001 ZZ/6202 ZZ also available with 6001 2RS/ 6202 2RS (AT1K 1/2z11,RS,Stau "EK") and counterbearing 024E with 6002 ZZ also available with 6002 2RS (024RS). Axle with inside thread M8x15 on both sides. By adjusting the nuts on the fine thread,M12x1.25 the friction of the chain wheel as well as the anti-friction bushing and thus the drive force is increased.

Maximum allowed conveying speed 0.5 m/sec.

Stau = Friction

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	024											
50x1,5	12	●	●	○	●	●			●	60											
50x2	12	●	●	○	●	●				60											
50x2,8	12						●	●		60											
60x1,5	12	●	●	○	●					60											
60x2	12	●	●	○	●					60											
60,3x1,65	12					●				60											
63x3	12						●	●		60											

Counter-bearing	Pipe-Ø	Axle-Ø	EL =	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposed external thread BG	
024E		12	RL +	59						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
 ● - In the standard


Ordering example

AT1K 1/2z11,Stau "EK"
024E-50x1,5 SV A12 IG8x15 EL=567

Powered conveyor roller with single chain wheel




AT1K 1/2z11,verschweisst



Steel chain wheel 1/2"x5/16" z11 with rack and pinion gearing welded with pipe.



Grooved ball bearing 6202 also available as ZZ or 2RS.



a=12mm, b=15,5mm, T=45,07mm, N=31,5mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	013	017	021	021N	025	028	029	
50x1,5	10,12,14	●	●	○	●	●				100	100	100	60	100		100	
50x2	10,12,14	●	●	○	●					100	100	100	60	100	100	100	
50x3	10,12,14	●	●	○	●						100			100			
60x1,5	10,12,14	●	●	○	●					100	100	100	60	100		100	
60x2	10,12,14	●	●	○	●					100	100	100	60	100	100	100	
63,5x2,9	10,12,14	●	●	○								100	60	100	100		
80x2	10,12,14	●	●	○	●	●				100	100	100	60	100		100	

Counter-bearing	Pipe-Ø	Axle-Ø	EL=							
				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
013		10,12	RL+	31						6
017		10,12,14	RL+	34						7
021/021N		10,12,14	RL+	31						10
025		10,12,14	RL+	31						10
028		10,12,14	RL+	37						7
029		10,12,14	RL+	33						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT1K 1/2z11,verschweisst
025-50x1,5 SV A12 IG8x15, EL=432

Powered conveyor roller with single chain wheel




AT1K 1/2z14,K,Stau / AT1K 1/2z14,K,Fest



Chain wheel 1/2"x5/16" z14 of thermoplastic material as an accumulation drive (Friction) or as fixed drive (Fixed) with press fit. Grooved ball bearing 6202 also available as ZZ or 2RS.

Not suitable for stop and go as fixed drive.

For information on accumulation drive, see Page 4.



a=11,5mm, b=18mm, T=57,07mm, N=43mm

Stau = Friction

Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029
50x1,5	10,12,14	●	●	○	●	●			●	24	24	40	40	40	40	40	40	40	40
50x2	10,12,14	●	●	○	●	●							40	40	40	40	40	40	40
50x2,8	10,12,14						●	●		24	24	40			40	40	40		
50x3	10,12,14	●	●	○	●									40			40		
60x1,5	10,12,14	●	●	○	●					24	24	40	40	40	40	40	40		40
60x2	10,12,14	●	●	○	●								40	40	40	40	40	40	40
60,3x1,65	10,12,14					●				24	24	40			40	40	40		40
63x3	10,12,14						●	●		24	24	40			40	40	40		
63,5x2,9	10,12,14	●	●	○											40	40	40	40	
80x2	10,12,14	●	●	○	●	●							40	40	40	40	40		40

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
009/009N	●	●		10,12	RL+	35						8
011	●	●		10,12	RL+	35						9
013	●	●		10,12	RL+	34						6
017	●	●		10,12,14	RL+	36						7
021/021N	●	●		10,12,14	RL+	35						10
025	●	●		10,12,14	RL+	35						10
028	●	●		10,12,14	RL+	39						7
029		●		10,12,14	RL+	37						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 1/2z14,K,Stau
025-50x1,5 SV A12 IG8x15, EL=432


Powered conveyor roller with single chain wheel



AT1K 1/2z14,S,Stau / AT1K 1/2z14,S,Fest



Steel chain wheel 1/2"x5/16" z14 with rack and pinion gearing as accumulation drive (Friction) or as fixed drive (Fixed) with press fit grooved ball bearing 6202 also available as ZZ or 2RS.
Not suitable for stop and go as fixed drive.



a=11,5mm, b=18mm, T=57,07mm, N=43mm

For information on accumulation drive, see Page 4.

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029
50x1,5	10,12,14	●	●	○	●	●			●	24	24	100	100	100	100	60	100		100
50x2	10,12,14	●	●	○	●	●							100	100	100	60	100	100	100
50x2,8	10,12,14						●	●		24	24	100			100	60	100		
50x3	10,12,14	●	●	○	●									100			100		
60x1,5	10,12,14	●	●	○	●					24	24	100	100	100	100	60	100		100
60x2	10,12,14	●	●	○	●	●							100	100	100	60	100	100	100
60,3x1,65	10,12,14					●				24	24	100			100	60	100		100
63x3	10,12,14						●	●		24	24	100			100	60	100		
63,5x2,9	10,12,14	●	●	○											100	60	100	100	
80x2	10,12,14	●	●	○	●	●							100	100	100	60	100		100

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
009/009N	●	●		10,12	RL+	35						8
011	●	●		10,12	RL+	35						9
013	●	●		10,12	RL+	34						6
017	●	●		10,12,14	RL+	36						7
021/021N	●	●		10,12,14	RL+	34						10
025	●	●		10,12,14	RL+	34						10
028	●	●		10,12,14	RL+	39						7
029		●		10,12,14	RL+	36						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 1/2z14,S,Stau
025-50x1,5 SV A12 IG8x15, EL=432

Adjustable friction roller



AT1K 1/2z14,S,Stau "EK"



a = 11,5mm
b = 18mm
f = 2mm
h = 29mm
N = 43mm
T = 57,07mm

Steel chain wheel 1/2"x5/16" z14 as accumulation drive with adjustable drive force. Drive head with grooved ball bearing 6202 ZZ also available with 6202 2RS (AT1K 1/2z14,RS,Stau "EK") and counterbearing 024E with 6002 ZZ also available with 6002 2RS (024RS). Axle with inside thread M8x15 on both sides.

By adjusting the nuts on the fine thread M12x1.25, the friction of the chain wheel as well as the anti-friction bushing and thus the drive force is increased.

Maximum allowed conveying speed 0.5 m/sec.

Stau = Friction

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	024									
50x1,5	12	●	●	○	●	●			●	60									
50x2	12	●	●	○	●	●				60									
50x2,8	12						●	●		60									
60x1,5	12	●	●	○	●					60									
60x2	12	●	●	○	●					60									
60,3x1,65	12					●				60									
63x3	12						●	●		60									

Counter-bearing	Pipe-Ø	Axle-Ø	EL =	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
024E		12	RL +	61						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 1/2z14,Stau "EK"
024E-50x1,5 SV A12 IG8x15, EL=567


Powered conveyor roller with single chain wheel



AT1K 1/2z14,verschweisst






Steel chain wheel 1/2"x5/16" z14 with rack and pinion gearing welded with pipe. Grooved ball bearing 6202/6003 also available as ZZ or 2RS.



a=11,5mm, b=18mm, T=57,07mm, N=43mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	013	017	021	021N	025	028	029	
50x1,5	10,12,14,15,17	●	●	○	●					150	150	150	60	150		150	
50x2	10,12,14,15,17	●	●	○	●					150	150	150	60	150	150	150	
50x3	10,12,14,15,17	●	●	○	●						150			150			
60x1,5	10,12,14,15,17	●	●	○	●					150	150	150	60	150		150	
60x2	10,12,14,15,17	●	●	○	●					150	150	150	60	150	150	150	
63,5x2,9	10,12,14,15,17	●	●	○								150	60	150	150		
80x2	10,12,14,15,17	●	●	○	●					150	150	150	60	150		150	

Counter-bearing		Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG						
013			10,12	RL+	35						6
017			10,12,14	RL+	37						7
021/021N			10,12,14	RL+	33						10
025			10,12,14,15,17	RL+	33						10
028			10,12,14,15,17	RL+	40						7
029			10,12,14,15,17	RL+	35						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT1K 1/2z14,verschweisst
025-50x1,5 SV A12 IG8x15, EL=432

Powered conveyor roller with single chain wheel




AT1K 5/8z12,S,Stau / AT1K 5/8z12,S,Fest



Steel chain wheel 5/8"x3/8" z12 with rack and pinion gearing as accumulation drive (Friction) or as fixed drive (Fixed) with press fit grooved ball bearing 6202/6003 also available as ZZ or 2RS.
Not suited for stop and go operation as fixed drive.

For information on accumulation drive, see page 4.



a = 15mm, b = 28mm, T = 61,34mm, N = 36mm

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	017	025	028	029				
50x1,5	12,14,17	●	●	○	●	●			●	100	100		100				
50x2	12,14,17	●	●	○	●	●				100	100	100	100				
50x3	12,14,17	●	●	○	●					100	100		100				
60x1,5	12,14,17	●	●	○	●					100	100		100				
60x2	12,14,17	●	●	○	●	●				100	100	100	100				
60,3x1,65	12,14,17					●					100		100				
63,5x2,9	12,14,17	●	●	○							100	100	100				
80x2	12,14,17	●	●	○	●	●				100	100		100				

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
017	●	●		12,14	RL+	49						7
025	●	●		12,14,17	RL+	47						10
028	●	●		12,14,17	RL+	52						7
029				12,14,17	RL+	49						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT1K 5/8z12,verschweisst
029-63,5x2,9 SV A14 IG8x15, EL=432


Powered conveyor roller with single chain wheel



AT1K 5/8z12,verschweisst






Steel chain wheel 5/8"x3/8" z12 with rack and pinion gearing welded with pipe.
Grooved ball bearing 6204 also available as ZZ or 2RS.



a = 18mm, b = 18mm, T = 61,34mm, N = 44mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	033											
80x2	20	●	●	○	●					400											
80x3	20	●	●	○	●					400											
88.9x2.9	20	●	●	○	●					400											
108x3.6	20	●	●	○	●					400											

Counter-bearing	Pipe-Ø	Axle-Ø	EL=							
				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
033		20	RL+	41						

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT1K 5/8z12,verschweisst
033-88.9x2,9 SV A20 IG10x15, EL=432

Powered conveyor roller with single chain wheel




AT1K 5/8z12,S,Stau / AT1K 5/8z13,S,Stau / AT1K 5/8z15,S,Stau



Steel chain wheel 5/8"x3/8" z12 with rack and pinion gearing as accumulation drive (Friction). Grooved ball bearing 6204/6004 also available as ZZ or 2RS.

For information on accumulation drive, see page 4.

Stau = Friction



z12: a = 18mm, b = 18mm, T = 61.34mm, N = 36mm
 z13: a = 18mm, b = 18mm, T = 66.32mm, N = 51mm
 z15: a = 18mm, b = 18mm, T = 76.36mm, N = 60mm

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	034	037	044							
80x2	17/20	●	●	○	●	●				200	200	200							
88,9x2,9	17/20	●	●	○	●	●				200	200	200							

Counter-bearing	Pipe-Ø	Axle-Ø				EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		z12	z13	z15									
034		17	20	17/20	RL+	43							8
037		17	20	17/20	RL+	43							10
044		17	20	17/20	RL+	43							8

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
 ● - In the standard


Ordering example

AT1K 5/8z13,S,Stau
 034-88,9x2,9 SV A20 IG12x18, EL=432


Powered conveyor roller with single chain wheel



AT1K 5/8z13,verschweisst / AT1K 5/8z15,verschweisst






Steel chain wheel 5/8"x3/8" z13 or z15 with rack and pinion gearing welded with pipe.
Grooved ball bearing 6204 also available as ZZ or 2RS.



with z13: a = 18mm, b = 18mm, T = 66,32mm, N = 51mm
with z15: a = 18mm, b = 18mm, T = 76,36mm, N = 60mm

verschweisst = welded

Pipe-Ø	z13	z15	Pipe design								Maximum load bearing capacity per roller*											
	Axle-Ø		S	SV	SG	SP	N	PG	PB	ALU	033	045										
63,5x2,9	20		●	●	○						480											
80x2	20		●	●	○	●					480											
80x3	20		●	●	○	●					480											
88,9x2,9	20	25	●	●	○	●					480	480										
108x3,6	20	25	●	●	○	●					480	480										
133x4	20	25	●	●	○	●						480										

Counter-bearing	Pipe-Ø	Axle-Ø	EL=							
				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
033		20,25	RL+	41						8
045		20,25	RL+	41						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT1K 5/8z15,verschweisst
033-88,9x2,9 SV A20 IG10x15, EL=967


Powered conveyor roller with single chain wheel



AT1K 3/4z13,verschweisst




Steel chain wheel 3/4"x7/16" z13 with rack and pinion gearing with pipe welded. Grooved ball bearing 6204/6005 also available as ZZ or 2RS.



a = 18mm, b = 18mm, T = 79,59mm, N = 60mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	033	045								
80x2	20,25	●	●	○	●					480									
80x3	20,25	●	●	○	●					480									
88,9x2,9	20,25	●	●	○	●					480									
108x3,6	20,25	●	●	○	●					480									
133x4	20,25	●	●	○	●						480								

Counter-bearing	Pipe-Ø	Axle-Ø	EL=	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG						
				IG	S	F	G	AG	BG	
033		20,25	RL+	41						8
045		20,25	RL+	41						10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.

○ - Design upon request
● - In the standard

Ordering
example

AT1K 3/4z13,verschweisst
033-88,9x2,9 SV A20 IG10x15, EL=967




Centre distances for chains

Chain links	3/8" x 7/32" z=12	1/2" x 5/16" z=14	5/8" x 3/8" z=15	3/4" x 7/16 z=13	
22	47,6				
24	57,2				
26	66,7	76,2		123,8	
28	76,2	88,9	103,2	142,9	
30	85,8	101,6	119,1	161,9	
32	95,3	114,3	134,9	181,0	
34	104,8	127,0	150,8	200,0	
36	114,3	139,7	166,7	219,1	
38	123,9	152,4	182,6	238,1	
40	133,4	165,1	198,5	257,2	
42	142,9	177,8	214,3	276,2	
44	152,4	190,5	230,2	295,3	
46		203,2	246,1	314,3	
48		215,9	261,9	333,4	
50		228,6	277,8	352,4	
52		241,3	293,7	371,5	
54		254,0	309,6	390,5	
56		266,7	325,4	409,6	
58		279,4	341,3	428,6	
60		292,1	357,2	447,7	


Centre distance für ribbed belt

Number of ribbings	Designation					Conveyor weight
	PJ 256	PJ 286	PJ 336	PJ 376		
2	60	75	100	120		1-40kg
3	60	75	100	120		41-200kg


Other designs upon request




Powered conveyor roller with double chain wheel



AT2K 3/8z12,S,Stau / AT2K 3/8z12,S,Fest



Steel chain wheel 3/8"x7/32" z12 with Plain toothing als accumulation drive (Friction) or as fixed drive (Fixed) with press fit. Grooved ball bearing 608 ZZ also available as 2RS. Not suitable for stop and go as fixed drive.



For information on accumulation drive, see Page 4.

a = 9,5mm, b = 20mm, c = 12,5mm, T = 36,8mm
N = 27mm

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*					
		S	SV	SG	SP	N	PG	PB	ALU	001	001N	005			
30x1	8	●	●	○	●	●				14	14	40			
30x1,8	8						●	●		14	14	40			
32x2	8	●	●	○	●	●				14	14	40			

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
001/001N	●	●	8		RL+					52		11
005	●	●	8		RL+					50		6

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT2K 3/8z12,S,Fest
005-30x1 SV A8 AG8x15, EL=432


Powered conveyor roller with double chain wheel



AT2K 1/2z14,K,Stau / AT2K 1/2z14,K,Fest



Chain wheel 1/2"x5/16" z14 of thermoplastic material as accumulation drive (Friction) or as fixed drive (Fixed) with press fit. Grooved ball bearing 6202 also available as ZZ or 2RS. Not suitable for stop and go as fixed drive.



a = 11,5mm, b = 21mm, c = 18mm, T = 57,07mm
N = 42mm

For information on accumulation drive, see Page 4.

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029
50x1,5	10,12,14	●	●	○	●	●			●	24	24	40	40	40	40	40	40	40	40
50x2	10,12,14	●	●	○	●	●							40	40	40	40	40	40	40
50x2,8	10,12,14						●	●		24	24	40			40	40	40		
50x3	10,12,14	●	●	○	●									40			40		
60x1,5	10,12,14	●	●	○	●					24	24	40	40	40	40	40	40		40
60x2	10,12,14	●	●	○	●								40	40	40	40	40	40	40
60,3x1,65	10,12,14					●				24	24	40			40	40	40		40
63x3	10,12,14						●	●		24	24	40			40	40	40		
63,5x2,9	10,12,14	●	●	○											40	40	40	40	
80x2	10,12,14	●	●	○	●	●							40	40	40	40	40		40

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
	Friction	Fixed										
009/009N	●	●		10,12	RL+	56						8
011	●	●		10,12	RL+	56						9
013	●	●		10,12	RL+	55						6
017	●	●		10,12,14	RL+	57						7
021/021N	●	●		10,12,14	RL+	57						10
025	●	●		10,12,14	RL+	57						10
028	●	●		10,12,14	RL+	61						7
029				10,12,14	RL+	58						7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.*


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering example

AT2K 1/2z14,K,Stau
025-50x1,5 SV A12 IG8x15, EL=432

Powered conveyor roller with double chain wheel




AT2K 1/2z14,S,Stau / AT2K 1/2z14,S,Fest



Steel chain wheel 1/2"x5/16" z14 as accumulation drive (Friction) or as fixed drive (Fixed) with press fit. Grooved ball bearing 6202 also available as ZZ or 2RS.
Not suitable for stop and go as fixed drive.


For information on accumulation drive, see Page 4.



a = 11,5mm, b = 21mm, c = 18mm, T = 57,07mm
N=43mm

Stau = Friction / Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*										
		S	SV	SG	SP	N	PG	PB	ALU	009	009N	011	013	017	021	021N	025	028	029	037
50x1,5	12,14	●	●	○	●	●			●	24	24	100	100	100	100	60	100		100	
50x2	12,14	●	●	○	●	●							100	100	100	60	100	100	100	
50x2,8	12,14						●	●		24	24	100			100	60	100			
50x3	12,14	●	●	○	●									100			100			
60x1,5	12,14	●	●	○	●					24	24	100	100	100	100	60	100		100	
60x2	12,14	●	●	○	●								100	100	100	60	100	100	100	
60,3x1,65	12,14					●				24	24	100			100	60	100		100	
63x3	12,14						●	●		24	24	100			100	60	100			
63,5x2,9	12,14,17	●	●	○											100	60	100	100		100
80x2	12,14,17	●	●	○	●	●							100	100	100	60	100		100	100

Counter-bearing			Pipe-Ø	Axle-Ø	EL=	     						
	Friction	Fixed				IG	S	F	G	AG	BG	
009/009N	●	●		12	RL+	56						8
011	●	●		12	RL+	56						9
013	●	●		12	RL+	55						6
017	●	●		12,14	RL+	57						7
021/021N	●	●		12,14	RL+	55						10
025 / 026	●	●		12,14	RL+	54						10
028	●	●		12,14	RL+	60						7
029		●		12,14	RL+	57						7
037	●	●		17	RL+	57						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT2K 1/2z14,S,Stau
025-50x1,5 SV A12 IG8x15, EL=432

Adjustable friction roller



AT2K 1/2z14,S,Stau "E"




a = 11.5mm
b = 21mm
c = 18mm
h = 29mm
N = 43mm
T = 57,07mm

Steel chain wheel 1/2"x5/16" z14 as accumulation drive with adjustable drive force. Drive head with grooved ball bearing 6001 ZZ also available with 6001 2RS (AT1K 1/2z14,RS, Stau "E") and counterbearing 024E with 6202 ZZ also available with 6202 2RS (024RS). Axle with internal thread M8x15 on both sides.
By adjusting the nuts on the fine thread M12x1.25, the friction on the friction disc and thus the drive force is increased.

Maximum allowed conveying speed 0.5 m/sec.

Stau = Friction

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*											
		S	SV	SG	SP	N	PG	PB	ALU	024											
50x1,5	12	●	●	○	●	●			●	60											
50x2	12	●	●	○	●	●				60											
50x2,8	12						●	●		60											
60x1,5	12	●	●	○	●					60											
60x2	12	●	●	○	●					60											
60,3x1,65	12					●				60											
63x3	12						●	●		60											

Counter-bearing	Pipe-Ø	Axle-Ø	EL=							
				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
024E		12	RL +	80						10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
● - In the standard

Ordering
example

AT2K 1/2z14,Stau "E"
024E-50x1,5 SV A12 IG8x15, EL=567



AT2K 1/2z14,S,Stau "EK"



a = 11.5mm
 b = 21mm
 c = 18mm
 f = 2mm
 h = 29mm
 N = 43mm
 T = 57,07mm

Steel chain wheel 1/2"x5/16" z14 as accumulation drive with adjustable drive force. Drive head with grooved ball bearing 6202 ZZ also available with 6202 2RS (AT2K 1/2z14,RS, Stau"EK") and counterbearing 024E with 6202 ZZ also available with 6202 2RS (024RS). Axle with internal thread M8x15 on both sides. By adjusting the nuts on the fine thread M12x1.25, the friction of the chain wheel in the anti-friction bushing and thus the drive force is increased. Maximum allowed conveying speed 0.5 m/sec.

Stau = Friction

Pipe- Ø	Axle- Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	024									
50x1,5	12	●	●	○	●	●			●	60									
50x2	12	●	●	○	●	●				60									
50x2,8	12						●	●		60									
60x1,5	12	●	●	○	●					60									
60x2	12	●	●	○	●					60									
60,3x1,65	12					●				60									
63x3	12						●	●		60									

Counter-bearing	Pipe-Ø	Axle-Ø	EL =	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposed external thread BG	
024E		12	RL +	81						10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


○ - Design upon request
 ● - In the standard

Ordering example	AT2K 1/2z14,Stau "EK" 024E-50x1,5 SV A12 IG8x15, EL=567
------------------	--


Powered conveyor roller with double chain wheel



AT2K 1/2z14,verschweisst



Steel chain wheel 1/2"x5/16" z14 welded with pipe. Grooved ball bearing 6202/6003 also available as ZZ or 2RS.



a = 11,5mm, b = 21mm, c = 18mm, T = 57,07mm
N = 43mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	013	017	021	021N	025	028	029	033		
50x1,5	12,14,15,17	●	●	○	●					150	150	150	60	150	150	150			
50x2	12,14,15,17	●	●	○	●					150	150	150	60	150	150	150			
50x3	12,14,15,17	●	●	○	●						150			150					
60x1,5	12,14,15,17	●	●	○	●					150	150	150	60	150		150			
60x2	12,14,15,17	●	●	○	●					150	150	150	60	150	150	150			
63,5x2,9	12,14,15,17,20	●	●	○	●							150	60	150	150		150		
80x2	12,14,15,17,20	●	●	○	●					150	150	150	60	150		150	150		
88.9x2.9	17,20	●	●	○	●												150		

Counter-bearing	Pipe-Ø	Axle-Ø	EL=	Internal thread						Smooth	External thread	Deposited external thread
				IG	S	F	G	AG	BG			
013		12	RL+	55								6
017		12,14	RL+	57								7
021/021N		12,14	RL+	55								10
025		12,14,15,17	RL+	55								10
028		12,14,15,17	RL+	60								7
029		12,14,15,17	RL+	55								7
033		17,20	RL+	55								7

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT2K 1/2z14,verschweisst
025-50x1,5 SV A12 IG8x15, EL=550

Powered conveyor roller with double chain wheel




AT2K 5/8z13,S,Stau / AT2K 5/8z15,S,Stau



Steel chain wheel 5/8"x3/8" z13 or z15 as accumulation drive. Grooved ball bearing 6204/6004 ZZ also available as 2RS.

For information on accumulation drive, see Page 4.

Stau = Friction



a = 18mm, b = 26mm, c = 18mm
bei z13: T = 66,32mm, N = 51mm
bei z15: T = 76,36mm, N = 60mm

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	034	037	044							
80x2	17/20	●	●	○	●	●				200	200	200							
88,9x2,9	17/20	●	●	○	●	●				200	200	200							

Counter-bearing	Pipe-Ø	Axle-Ø		EL=	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
		z13	z15								
034		20	17/20	RL+	69						8
037		20	17/20	RL+	69						10
044		20	17/20	RL+	69						8

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

AT2K 5/8z13,S,Stau
037-88,9x2,9 SV A20 IG12x18, EL=967


Powered conveyor roller with double chain wheel



AT2K 5/8z13,verschweisst / AT2K 5/8z15,verschweisst




Steel chain wheel 5/8"x3/8" z13 or z15 welded with pipe. Grooved ball bearing 6204/6005 also available as ZZ or 2RS.



a = 18mm, b = 26mm, c = 18mm
with z13: T = 66,32mm, N = 51mm
with z15: T = 76,36mm, N = 58mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	033	045	046	047				
63,5x2,9	20	●	●	○						560	560	560	560				
80x2	20,25	●	●	○	●					560	560	560	560				
80x3	20,25	●	●	○	●					560	560	560	560				
88,9x2,9	20,25	●	●	○	●					560	560	560	560				
108x3,6	20,25	●	●	○						560	560	560	560				
133x4	20,25	●	●	○							560	560	560				


Counter-bearing		Pipe-Ø	Axle-Ø	EL=							
					Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
033			20,25	RL+	67						8
045			20,25	RL+	67						10
046			20,25	RL+	67						10
047			20,25	RL+	67						10

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Ordering
example

AT2K 5/8z15,verschweisst
033-88,9x2,9 SV A20 IG10x15, EL=967


Powered conveyor roller with double chain wheel



AT2K 3/4z13,verschweisst




Steel chain wheel 3/4"x7/16" z13 welded with pipe.
Grooved ball bearing 6204/6005 also available as ZZ or 2RS.



a = 18mm, b = 30mm, c = 18mm, T = 79,59mm
N = 60mm

verschweisst = welded

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*							
		S	SV	SG	SP	N	PG	PB	ALU	033	045	046	047				
80x2	20,25	●	●	○	●					560	560	560	560				
80x3	20,25	●	●	○	●					560	560	560	560				
88,9x2,9	20,25	●	●	○	●					560	560	560	560				
108x3,6	20,25	●	●	○						560	560	560	560				
133x4	20,25	●	●	○						560	560	560					

Counter-bearing		Pipe-Ø	Axle-Ø	EL=							
					Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG	
033			20,25	RL+	71						8
045			20,25	RL+	71						10
046			20,25	RL+	71						10
047			20,25	RL+	71						10


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.

○ - Design upon request
● - In the standard

Ordering
example


AT2K 3/4z13,verschweisst
033-88,9x2,9 SV A20 IG10x15, EL=967




Various types of conical conveyor rollers are available:

1. Conical elements of thermoplastic material for internal radius of 500 or 800
2. PU or FBE-coated steel pipes according to any dimensions
3. Conical steel pipes uncoated, galvanised or stainless steel in any dimensions


Conical elements for internal radius of 500mm and pipe diameter of 30




Conical elements for internal radius of 800mm and pipe diameter of 50



Conical gravity conveyor roller



KST



Gravity conveyor roller with inserted conical elements of thermoplastic material.
Please find information on bearings with the corresponding gravity or powered conveyor roller.

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*									
		S	SV	SG	SP	N	PG	PB	ALU	001	001N	005	009	021	021N	025			
20x1.5	8	●	●			●				10	10								0
30x1	8,10	●	●			●				10	10	20							0
50x1,5	8,10,SK11,12,14	●	●			●										80			0
50x2,8	8,10,SK11,12,14						●	●					24	80	40	80			0

Counter-bearing	Pipe-Ø	Axle-Ø	EL =	 Internal thread IG  Spanner flat S  Spring axle F  Smooth G  External thread AG  Deposited external thread BG					
				IG	S	F	G	AG	BG
001/001N	20x1.5	8	RL +	22		22		35	
001/001N	30x1	8	RL +	23		23		36	
		10	RL +	23		23		33	
005	30x1	8	RL +					21	
		10	RL +	17					
021/021N		10	RL +	20	20	20	20	30	20
		SK11	RL +			20	20		
		12	RL +	20	20	20	20	32	20
		14	RL +	20	20	20	20	34	20
025		10	RL +	17	17	17	17	27	17
		SK11	RL +			17	17		17
		12	RL +	17	17	17	17	29	17
		14	RL +	17	17	17	17	31	17

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

- - Design upon request
- - In the standard

Ordering
example

KST/025-50x1,5 SV A12 IG8x15 EL=507

Conical conveyor roller with single chain wheel



KT1K 1/2z11,K,Fest / KT1K 1/2z14,K,Fest
KT1K 1/2z11,S,Fest / KT1K 1/2z14,S,Fest



	KT1K 1/2z11	KT1K 1/2z14
a =	12mm	11,5mm
b =	20,5mm	23mm
N =	30mm	43mm
T =	45,07mm	57,07mm

Powered conveyor roller with single chain wheel of thermoplastic material (KT1K 1/2z11,K,Fest / KT1K 1/2z14,K,Fest) or of steel (KT1K 1/2z11,S, Fest / KT1K 1/2z14,S,Fest) with inserted conical elements. Please find information on bearings with the corresponding gravity or powered conveyor roller.

Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*					
		S	SV	SG	SP	N	PG	PB	ALU	KT1K 1/2z11,K KT1K 1/2z14,K			KT1K 1/2z11,S KT1K 1/2z14,S		
										Ø1	Ø21	Ø25	Ø1	Ø21	Ø25
50x1,5	10,12,14	●	●			●						40			80
50x2,8	10,12,14						●			40	40	40	80	40	80

Chain wheel	Counter-bearing	Axle-Ø	EL =	Internal thread						Smooth	External thread	Deposited external thread	
				IG	S	F	G	AG	BG				
KT1K 1/2z11	021/021N	10,12,14	RL +	42									0
	025	10,12,14	RL +	42									0
KT 1K1/2z14	021/021N	10,12,14	RL +	45									0
	025	10,12,14	RL +	45									0

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.


Other designs upon request.

○ - Design upon request
● - In the standard

Ordering example


KT1K 1/2z11,K,Fest
025-50x1,5 SV A12 IG8x15, EL=542

Conical Conveyor roller with double chain wheel



KT2K 3/8z12,S,Fest

KT2K 1/2z14,K,Fest / KT2K 1/2z14,S,Fest



	KT2K 3/8z12	KT2K 1/2z14
a =	9mm	11,5mm
b =	20mm	21mm
c =	16mm	23mm
N =	27mm	43mm
T =	36,8mm	57,07mm

Powered conveyor roller with double chain wheel of thermoplastic material (KT2K 1/2z14,K,Fest) or of steel (KT2K 3/8z12,S,Fest / KT2K 1/2z14,S,Fest) with inserted conical elements.

Please find information on bearings with the corresponding gravity or powered conveyor roller.

Fest = Fixed

Pipe-Ø	Axle-Ø	Pipe design								Maximum load bearing capacity per roller*								
		S	SV	SG	SP	N	PG	PB	ALU	KT2K3/8z12,S			KT2K1/2z14,K			KT2K1/2z14,S		
										001	001N	005	021	021N	025	021	021N	025
30x1	8	●	●			●				10	10	20						
50x1,5	10,12,14	●	●			●									40			80
50x2,8	10,12,14						●	●					40	40	40	80	40	80

Chain wheel	Counter-bearing	Axle-Ø	EL =	Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposed external thread BG
KT2K 3/8z12	001/001N	8	RL +					64	0
	005	8	RL +					57	0
KT2K 1/2z14	021/021N	10,12,14	RL +	65					0
	025	10,12,14	RL +	65					0


* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3.

Other designs upon request.


- - Design upon request
- - In the standard

Ordering example


KT2K 1/2z14,K,Fest
025-50x1,5 S A12 IG8x15, EL=566



Conical Conveyor roller with multi-ribbed belt wheel



KT1MRI,K,Fest




$a = 12\text{mm}$, $b = 18.72\text{mm}$, $D = 43\text{mm}$

Powered conveyor roller with multi-ribbed belt wheel of thermoplastic material with inserted conical elements for curves up to a max. 5°.

Please find information on bearings with the corresponding gravity or powered conveyor roller.

Fest = Fixed

		Pipe design								Maximum load bearing capacity per roller*									
Pipe-Ø	Axle-Ø	S	SV	SG	SP	N	PG	PB	ALU	Ø25									
50x1,5	12,14	●	●			●				40									
50x2,8	12,14						●	●		40									

Counter-bearing		Axle-Ø	EL =	 Internal thread IG	 Spanner flat S	 Spring axle F	 Smooth G	 External thread AG	 Deposited external thread BG	
025		12,14	RL +	46						0

* - To determine the load bearing capacity of the axles and pipes, please use the chart on page 3. You can find

Information on centre distance on page 53.


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

KT1MRI,K,Fest
025-50x1,5 SV A12 IG8x15, EL=542

Conical conveyor roller with belt grooves



KATS



Belt groove conveyor roller with inserted conical elements of thermoplastic material.

Pipe-Ø	Axle-Ø	Pipe design				Belts-Ø	Minimum		Maximum		Minimum		Possible bearing	
		S	SV	N	PG		a	b	a+b	SD				c
50x1,5	10,SK11,12,14,15	●	●	●			5	30	30	120	40	10		025
50x1,5	10,SK11,12,14,15	●	●				6	30	30	120	38	10		025
50x2,8	10,SK11,12,14,15				●		5	30	30	97	40	10		025

Bearing	Pipe-Ø	Axle-Ø		Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
025		10	e =	8.5	8	8	8	13.5	
		SK11	e =			8	8		
		12	e =	8.5	8	8	8	14	
		14	e =	8.5	8		8	15.5	
		15*	e =	8	8		8		

			EL=						
025		10	RL+	12	11	11	11	22	12
		SK11	RL+			11	11		
		12	RL+	12	11	11	11	23	12
		14	RL+	12	11		11	26	12
		15*	RL+	11	11				12

* Labyrinth loose


Other designs upon request.

○ - Design upon request
● - In the standard


Ordering
example

KATS/025-50x2,8PG A12 S8x6 EL=372
- one-sided 2 belt grooves a=67, b=30, SD=40

Conical conveyor roller with round belt drive, Ri=260mm



KT2RR/049K,Fest



Powered conveyor roller with round belt wheel of thermoplastic material with inserted conical elements for internal radius $R_i=260\text{mm}$.
The grooved ball bearing 689ZZ is also available as 2RS (KT2RR/049K,RS,Fest) or INOX (KT2RR/049K,RSN,Fest).
Type 049K bearing seat of plastic.
Outside centre distance 57mm. Roller pitch 4.5° .

Internal- pipe-Ø	Axle-Ø	Pipe design				Belts-Ø			Maximum load bearing capacity per roller	
		S	SV	N		R	a	b	SD	
17x1,5	9	●	●	●		5	14	8	34.8	4


Bearing	Pipe-Ø	Axle-Ø	EL=						
				Internal thread IG	Spanner flat S	Spring axle F	Smooth G	External thread AG	Deposited external thread BG
049K	17x1.5	9	RL+	49					

Other designs upon request.


- - Design upon request
- - In the standard

Ordering example



KT2RR,K,Fest
049K-17x1.5S AN9 IG 6x10, EL=487




Guide discs




The masses of A and B must be specified when ordering conveyor rollers with guide discs.

	d	D		d	D
	30	60		60	110
	40	60			120
	50	70		63,5	130
				80	130
					135
					140
					150
				88,9	130
					135
					140
					150
				108	160

Back up rings


	RD	D	d	b
	63,5	108	60	25
	63,5	133	60	25
	88,9	133	85	30
	88,9	159	85	30
	108	159	104	30


















Buffer rings

	RD	D	d	b
	50	89	48	30
	63,5	89	60	25
	63,5	108	60	30
	88,9	133	86	35
	88,9	159	86	35

Other designs upon request.


Push-on caps




 Order number	 						
	Axlediameter AD	a	b	c	d	e	f
K0	15	9	5	11	15	28	20
A20 glatt/D=20							
 Order number	 						
	Axlediameter AD	s	a	b	c	d	e
K1	8	10	10	5	12,8	8	12
K2	8	14	10	5	12,8	8	16
K3	10	14	10	5	12,8	10	16
K3.01	10	12	9.5	5.5	13	10	16
K4	12	14	10	5	12,8	12	16
K5	14	17	10	5	12,8	14	21
SW 10x10/D=12 SW 14x10/D=16 SW 14x10/D=16 SW 12x9.5/D=16 SW 14x10/D=16 SW 17x10/D=21							
 Order number	 						
	Axlediameter AD	s	a	b	c	d	e
K6	20	30	13	3	36	15	20
SW 30x13/D=36							
 Order number	 						
	Axlediameter AD	s	a	b	c	d	e
K7	8	11	17	2,5	19	8,5	18
SK 11x17							
 Order number	 						
	Axlediameter AD	s	a	b	c	d	
K8	8	11	11	2,5	7,8	18	
K9	8	11	11	2,5	8,5	18	
SK 11x11 SK 11x11 F							
 Order number	 						
	Axlediameter AD	s	a	b	c	e	
K10	10	12	8	2	9.8	16	
SW 12x8/D=16							

Push-on caps of thermoplastic material
Other designs upon request.


Ordering example A12 **K4** (Axle Ø12 uncoated, both side with push-on cap K4)






Mini rollers, ball bearing mounted and with hardened or plastic running surface
Phosphatised surface

PEKO Article No.	Mini roller Dimensions	PEKO Article No.	Split mini roller Dimensions
MR-19/26 A6 C=1750N C0=1200N		SUMR-18/19 AG8x16 S10 sealed C=1500N C0=1000N	
MR-19/26 A8 C=1100N C0=800N		SUMR-21/25 AG8x16 S10 Plastic cap POM natural	
MR-19/9 A6 C=1600N C0=1000N		SUMR-12/12 AG6x11.5 S7 C=800N C0=450N	
MR-18/16 A6 C=1250N C0=800N		SUMR-12/18 AG6x11 S7 C=800N C0=450N	
MR-12/16 A4 C=800N C0=450N		SUMR-18/19 AG8x16 S10 C=1500N C0=1000N	
MR-15/26 A6 C=1100N C0=750N		SUMR-15/25 AG6x11 S10 C=1200N C0=800N	
MR-24/26 A6 Plastic cap POM natural		PEKO ROLLEN AG Langenhagstrasse 13, CH-9424 Rheineck Tel.+41 71 888 08 44, Fax +41 71 888 08 47 info@peko.ch / www.peko.ch	



Conveyor wheels of thermoplastic material		Conveyor wheels of galvanised steel	
ST-065 	ST-069 	ST-073 	ST-079

Multi-directional rollers of thermoplastic material				
ST-080 one piece	D	d	B	C
	40	8	26	29
	48	8	37	39
	60	8	47	48
	80	8	60	64
	120	12	86	90
ST-081 two pieces	D	d	B	C
	50	8	19,5	39
	60	8	25	51
	80	8	30	60



All roller tracks and guide tracks are available in fixed lengths according to your requirements (max. length 3000 mm). The wheels can be used in temperature ranges from -30°C to + 100°C.

Design with plain wheel:

Order no.: N 33 - length
Order no.: N 50 - length
Order no.: N 66 - length
Order no.: N 83 - length
Order no.: N 100 - length

Design with flanged wheel:

Order no.: SP 50 - length
Order no.: SP 66 - length
Order no.: SP 83 - length
Order no.: SP 100 - length

The following special wheels are available:

- Deep freeze design from -30°C
- Highly conductive wheel to prevent static charging (colour black).




If, with the fixed wheel track, a free dimensioning (S1 or S2) is to be in the front and rear, these dimensions must be specified. Your dimension specifications are our minimum dimensioning for the mounting. With flanged roller tracks, unequal free dimensions must be ordered for the right and left roller tracks. If you do not order free sizes the roller tracks are always to be mounted so that no wheel juts out. The wheel start varies, however, by the wheel pitch. If the wheels are to be started with exactly defined dimensioning, additional cut costs will be necessary.

Special cut:

Order no.: /SKF

To order fix roller tracks:

The pitches specified in the catalogue 33, 50 etc. are only approximate. The exact hole matrix in the fix wheel track is 16.667 mm +/- 0.1 mm.




Fix-Röllchenleiste - Toleranzen
Wheel channels - Tolerances

Please take the specified tolerances into account. If you would like to exactly specify the wheel start "S" (centre axle) (in connection with special cut order no.: /SKF), we can only comply with the exact dimension on this side. On the other side, you can only specify one size which, depending on the roller track length, phases out with the tolerances of the hole pitches (max. up to +/- 8.5 mm).

Axle and profiles in stainless steel

Order no.: (normal order no.)/VA



The axle can also be individually supplied in stainless steel. Order no.: AE



Expansion lock:

The expansion lock consists of a specially bent and hardened spring steel wire with a diameter of 1.5 mm and prevents an expansion of the fix wheel track with greater loads. The lock is clamped in a free axle mounting.


Order no.: SpS



Special designs of plain wheel:

Wheel highly conductive (wheel black)
Order no.: NHL-

Wheel colour black
Order no.: NSchw-





Special designs of flanged wheel:

Wheel highly conductive (wheel black)
Order no.: SPHL-

Fix-Röllchenleiste mit Mininormalröllchen
T = 16, 33, 50
EUROROLL Wheel Channels. Mini Normal' Wheels
T = 16, 33, 50

Fix roller tracks can be equipped with different wheels. In this way, all demands of the market and application are satisfied.





Fix wheel track with mini normal wheels:

Order no.: N mini 16 - length
Order no.: N mini 33 - length
Order no.: N mini 50 - length


Fix-Röllchenleiste mit Minispurkranzröllchen
T = 33, 50, 66
EUROROLL Wheel Channels. Mini Flanged Wheels
T = 33, 50, 66

Also available in highly conductive design (black).



Fix wheel track with mini flanged wheels:

Order no.: SP mini 33 - length
Order no.: SP mini 50 - length
Order no.: SP mini 66 - length



The main area of use of the superfix roller track is in flow racks for the secure running of heavy transport boxes and cartons. The wheels consist of high quality thermoplastic material which is impact and break-resistant. The material does not absorb moisture and is resistant to acids and lye. The wheels mounted on steel axles have a load capacity of 12 kg and are available as plain and flanged wheels. The roller track profile consists of cold-profiled, sendzimir galvanised steel profiles 1.5 mm thick.

All roller tracks are supplied in fixed lengths according to your wishes (max. length 3000 mm). Resistance torque $W_y = 1.2 \text{ cm}^3$.

Design with plain wheel

Ordering example:

Order no.: SFN - (pitch) / length

Pitch:

33 mm SFN - 33 / length

50 mm SFN - 50 / length

66 mm SFN - 66 / length

100 mm SFN - 100 / length

Design with flanged wheel

Ordering example:

Order no.: SFSP - (pitch) / length

Pitch:

50 mm SFSP - 50 / length

66 mm SFSP - 66 / length

100 mm SFSP - 100 / length

Special cut:

Order no.: /SKSF

Single wheels (incl. steel axles) Plain

roll:

Order no.: SFN

Flanged roll:

Order no.: SFSP

Accessories

End stop:

Order no.: ESF


Loop delayed End stop:

Order no.: ESchESF

Connector:


The connector consists of u- profiles which are mounted with 4 screws under the wheel track.

Order no. VSF




To order the superfix-roller tracks:

Any length can be ordered. Try to order lengths in the hole matrix of 16.67 mm. Example: The last two digits of the length ordered should be 00, 16, 33, 50, 66, 83. Special cuts with defined wheel starts SI are possible. For the installation in flow racks, free dimensioning is required. Please specify this in the order.



The bearing lengths of the universal roller tracks is 3000 mm. As a rule, we supply you with any desired fix length. The profiles is sendzimir galvanised, $W_y = 2.2\text{cm}^3$. Plain wheels are, if not specially ordered, mounted in the lower holes, flanged wheels are always mounted in the upper holes.

Universal-Rollenschiennenprofil
Universal Roller Tracks Profile



Profiles without roll:

Order no.: U28

The following wheels are available:

ball bearing mounted:

Plain roll, $\varnothing 48$ mm, plastic

Payload 10 kg

Order no.: NR10

Plain roll, steel galvanised, Payload 20 kg

Order no.: NR20

Flanged roll, plastic, Payload 10 kg


Order no.: SR10

Flanged roll, steel, Payload 20 kg

Order no.: SR21

All plain wheels can be coated with a buffer ring of PUR. Order no.: PUR

Abmessungen Röllchen
Dimension wheels



Friction bearing:

All friction bearing wheels have a minimum payload of 10 kg. The running surface of the friction bearing wheels is slightly spherical.

Plain roll, design polypropylene

colour: blue (hard plastic)

Order no.: NRGH

Plain roll, design PUR colour: yellow


(soft plastic)

Order no.: NRGW


The wheels NR10, NR20, SR10 and SR21 are mounted with tubular rivets and cover cap (rounded).

Order no.: HIN

Hauptabmessungen mit Kunststoff-Röllchen
Main dimension with plastic wheels



Hauptabmessungen mit Stahlröllchen
Main dimension with steel wheels




Upon request, they can be mounted with special plastic screws.

Order no.: VS 26

The wheels NRG are mounted with galvanised steel screws.

Order no.: M 8 X 35

All wheels can be individually exchanged.



Universal roller track with flanged wheel SR21


SR21 has, in contrast to SR20 roller which is no longer or only in limited quantities available, a diameter of 50 mm instead of 48 mm. With the parallel use of SR21 and NR20, the height difference of 1 mm must be aligned to the support points of the plain roller track.

Ordering note:


Please specify the wheel type, the wheel pitch and the exact length (the length must be divisible by 25 mm) when ordering.

Ordering example: SR21 - 100/3000

Universal roller track with flanged steel wheels, 100 mm pitch, 3000 mm Total length



Please specify the wheel type, the wheel pitch and the exact length (the length must be divisible by 25 mm) when ordering.



Ordering example:

NR20 - 50/3000

Universal roller track with steel wheels, 50 mm pitch, 3000 mm Total length of the track

SR10 - 100/3000

Universal roller track with plastic wheels with flanges, 100 mm pitch, 3000 mm Total length of the track

Normalröllchen Plain wheels

T= 50, 75, 100, 125, 150 usw.

Accessories:

End stop:

Order no.: EU


Loop delayed end stop:


Order no.: EUS

Connector (incl. screws):

Order no.: VU

All wheels, screws, etc. can be individually ordered.





The Colli-roller track combines many advantages. It is the only solution for many logistic applications. In a sendzimir galvanised u-profile 50 x 58 x 50 x 2.5 mm, ball bearing mounted rollers are mounted exchangeably with a payload of 40 daN (kg). The roller Ø 54 mm is available as a normal roller or as a flanged roller. Of course, both roller types can also be supplied interchangeably or e.g. only for every 4th roller with flange in the track. The roller coat is of plastic, colour blue, material polypropylene. The load capacity of a roller track is calculated from the resistance torque of 3.0 cm³. Through the wide running surface, the Colli-roller track expands the universal-roller track's application. The application areas listed for this also apply to the Colli-roller track.

Profiles without roll
Order no.: U58

Plain wheel Ø 54
Order no.: NR40

Flanged wheel Ø 70/54
Order no.: SR40

Axle with lock nut
Order no.: M 8 X 70

The bearing length of the Colli-roller track profile is 3000 mm. As a rule, we can supply you any desired fix length. Please observe that you must specify a linear measurement whose last two digits are 00, 33 or 66 (e.g. 2333 or 2300 or 2366 or 2400 mm). Other lengths require a special cut.
Order no.: /SK

The following roller pitches are available: Plain roll: 66 mm, 100 mm, 133 mm, 166 mm, 200 mm. Flanged roll: 100 mm, 133 mm, 166 mm, 200 mm. Exchangeable flanged and normal roll: 66 mm, 100 mm, 133 mm, 166 mm, 200 mm.




Ordering examples:
SR 40-100/2000
Colli-roller track with flanged roll,
100 mm roller pitch, 2000 mm long.


NR/SR 40-66/3333
Colli-roller track exchangeable with normal and
flanged roll, 66 mm roller pitch,
3000 mm long.

Accessories:
End stop: Order no.: EC

Loop delayed end stop: Order no.: ESC

Roller protection: Order no.: RSC
Connector (incl. screws): Order no.: VUC





This multi-directional roller track is specified for light loads and is similar in design to the universal roller track. All accessories in this programme can be used such as e.g. end stop (Order no.: EU) or connector (Order no.: VU). The resistance torque of the roller track is 2.2 cm³. Load capacity per roller is 5 daN (kg). The bearing lengths of the Multi-directional roller tracks profil is 3000mm.

Ordering example:

Order no.: AR 10 - (pitch) / length

Pitch:

50 mm AR 10 - 50 / length

75 mm AR 10 - 75 / length

100 mm AR 10 - 100 / length

125 mm AR 10 - 125 / length

Please specify if the roller is to be mounted in the upper hole

Order no.: /0

or in the lower hole

Order no.: /U.

Single roller

Order no.: AR 10

Order in a grid of 25 mm, all other lengths require a special cut.

Order no.: SK

Suomi-multi-directional roller track for light loads

Order no.: ASRS 50

The load capacity per roller is 10 daN (kg).

This track is suited for a max. weight of goods to be conveyed of 100 daN (kg). The slight, lateral shift or rotation of conveyed goods requires a tight roller gap in both directions. This must be determined by tests if necessary. The resistance torque of the roller track is 2.2 cm³.

Ordering example:

Order no.: ASRS 50 - (pitch) / length

Pitch

66 mm ASRS 50 - 66 /length

100 mm ASRS 50 - 100 /length

133 mm ASRS 50 - 133 /length

166 mm ASRS 50 - 166 /length

Single roller


Order no.: ASR 50

Accessory:


End stop

Order no.: EA 50



Universal Allseitenrollenschiene
Multi-Directional Wheel Channel
AR 10






Rolle montiert in unterer Lochreihe
Wheel mounted in lower hole





Rolle montiert in oberer Lochreihe
Wheel mounted in upper hole



ASRS 50







The roller tracks consist of one sendzimir galvanised u-profiles, 55 mm high and 80 mm wide. These profiles are equipped with rollers, Ø 50 mm, or rolls Ø 48 mm, in pitches of 52, 78, 104, 130, 156 mm etc. Two other rows of holes in the floor are used for mounting this track on bases.

Wy: 4.6 cm³

ly: 17 cm³

Length: 3000 mm

Track without rollers:

Order no.: U 80 - 55

The pallet roller track can be equipped with various rollers.

3 normal rolls of plastic
(30 kg load capacity)

Order no.: NR 30

3 normal rolls of steel
(60 kg load capacity)

Order no.: NR 60

Steel rollers with 150 kg load capacity:

Order no.: NR 100

Steel rollers with flange:

Order no.: SR 100


The rolls and rollers are positioned on an axle with lock nuts

Order no.: M 8 X 90 A

Abbreviations for orders:

NR 100 (60) (30) = Type designation of the roller track


-52, -78, -104, -156 etc. roller pitch/2600
length of the roller track (the length should be divisible by 26 mm)



NR 100

NR 30 und NR 60
NR 30 and NR 60

SR 100



Rollenteilung: 52, 78, 104, 130, 156
Roller pitches: 52, 78, 104, 130, 156 a.s.o.

Accessories:

End stop: Order no.: EE

Sliding end stop: Order no.: ESchE

Connector as u-profile: Order no.: VE

Roller protection: Order no.: RSE


Lateral connection pieces (2 pieces): Order no.: USE Fixing

clip with screw: Order no.: BKE

Example:

NR 100 - 156 / 2600 roller track with Ø.50 mm steel rollers in 156 mm pitch, track: 2600 mm long.

The mounting with flanged rollers can be done so that e.g. only every 5th roller is mounted with a flange.



Brake rollers regulate the speed on gravity roller conveyors; they keep the goods being conveyed at a constant shunting speed. This is done using a planetary gear which presses centrifugal brake shoes on the roller with each rotation and this, with proportional braking force to the applied braking torque. The distance of the brake rollers and the right brake roller type are influenced by several factors:

- a) Design and functional performance of the roller conveyor
- b) incline of the roller conveyor
- c) Behaviour of the goods being conveyed (size, weight, sensitivity, runner material)
- d) Inherent resistance of brake roller
- e) Environmental influences such as moisture, cold or heat.

One brake roller per pallet position is ideal because this is the only way, a controlled speed can be achieved without accelerations and the occurrence of increased forces. The shunting speed should never exceed 0.3 m/sec. if the brake rollers are correctly aligned, they it is only 0.1 – 0.2 m/sec.

The brake roller is available with a short or long holder.

Order no.: -K or -L

With 4% incline, it is available for the following maximum braking payloads:
 300 kg Order no.: EBR 300 - (Holder)
 500 kg Order no.: EBR 500 - (Holder)
 800 kg Order no.: EBR 800 - (Holder)
 1000 kg Order no.: EBR 1000 - (Holder)
 1200 kg Order no.: EBR 1200 - (Holder)

Ordering example:

EBR 800 – L

Brake roller with long holder for
 800 kg/pallet

Support axle for mounting the
 brake roller

Order no.: AAB

Spring suspension in various lengths

A = 30 Order no.: FB 30

A = 40 Order no.: FB 40

A = 50 Order no.: FB 50

A = 65 Order no.: FB 65


Clip bolts in various lengths



H = 67 Order no.: HB 67

H = 88 Order no.: HB 88

Brake lining for the conveyor roller with
 indirect use

(Please give length L) Order no.: RNN - L







Braking force diagram for the right selection of the correct brake roller. Forces (which mainly result from acceleration) which exceed those in this diagram can destroy the brake roller and are therefore not permitted.

Direct deceleration:



With direct deceleration, the brake roller has direct contact to the goods being transported. It is suspended elastically and must be approx. 2 mm above the level.




Indirect deceleration:



Indirect deceleration is preferred in many cases because the contact to the pallet is transferred via 2 conveyor rollers. 4 springs take over the contact, 2 clip bolts, which are loosely installed, secure the brake rollers.

In order to improve the contact of the brake roller, conveyor roller and pallet, a self-adhesive friction lining is provided on the conveyor roller in the area of the brake roller.





The **PEKO clutch brake system KB1512** was specially developed for the transport of boxes, containers and cartons up to a weight of 40kg. Since it is an open system, no malfunction will occur due to pollution caused by abrasion. A simple function and wear control from the outside is possible. Due to very high wear resistance, many millions of switching cycles with high drive and braking torque are possible.




Clutch brake system:


Scope of delivery consists of:

- 1 unit clutch/brake incl. adapter plates and belt deflection wheel
- 1 unit sheet metal frame for cable attachment
- 1 unit clamping sheet (against hole pitch in side profile)
- 1 four-pole plug MKF 13264-6-0-404 AWG 24 Stocko (other design is possible)
- 4 conveyor rollers Ø50x1.5 (uncoated, galvanised or Niro), variable length
- 2 round belts Ø5 L=302mm (at p=75)
- 2 round belts Ø5 L=361mm (at p=125)
- Screws for mounting


Profile, control and drive are not part of scope of delivery!




The clutch brake system is to be driven by means of an endless flat belt $b=25\text{mm}$.




Gravity conveyor roller with smooth axle (G) or spring axle (F)




Gravity conveyor roller with external thread (AG)







Gravity conveyor roller with internal thread (IG)





Gravity conveyor roller with spanner flat (S)






Powered conveyor roller with belt grooves and internal thread (IG)







Powered conveyor roller
with tooth belt wheel and internal thread (IG)




Powered conveyor roller
with doubled tooth belt wheel and internal thread (IG)







Powered conveyor roller
with single chain wheel and internal thread (IG)




Powered conveyor roller
with single chain wheel and external thread (AG)







Powered conveyor roller
with double chain wheel and internal thread (IG)




Powered conveyor roller
with double chain wheel and external thread (AG)







Conical gravity conveyor roller
with inside thread (IG)




Conical Gravity conveyor
roller with spanner flat (S)







Conical gravity conveyor roller
with smooth axle (G) or spring axle (F)




Conical gravity conveyor roller with external thread (AG)







Conical conveyor roller
with single chain wheel and internal thread (IG)




Conical conveyor roller
with single chain wheel und external thread (AG)







Conical conveyor roller
with double chain wheel and internal thread (IG)




Conical Conveyor roller
with double chain wheel und external thread (AG)





PEKO inquiry form



Company:	Name:
Tel.:	Fax:
E-Mail:	

Gravity conveyor roller ☐
 Powered conveyor roller ☐

Quantity: _____ piece
 Load/Roller: _____ kg

If known PEKO type: _____

Roller length RL: _____ mm Installation length EL: _____ mm Axle length AL: _____ mm

Material data:

Pipe Ø	Wall thickness	Pipe material	Axle Ø	Axle design	Bearing type
16	1	steel uncoated	6	Internal thread ☐	Plastic with row of balls:
20	1.5	steel galvanised	8	IG x _____	Steel balls ☐ Niro balls ☐
30	1.8	Niro 1.4301	10	External thread ☐	Plastic with grooved ball bearing:
40	2	PVC blue	SK11	AG x _____	ZZ ☐ RS ☐ RSN ☐
50	2.3	PVC gray	12	Spanner flat ☐	Sheet steel with cone bearing ☐
60	2.8	ALU	14	SW x _____	Steel with grooved ball bearing:
63	2.9		15	Spring axle ☐	ZZ ☐ RS ☐ RSN ☐
63.5	3		17	Smooth axle ☐	
70	3.6		20		
80	4		25		
88.9	4.5		30		
101.6					
108					
133					
159					

rubber coating		PVC tube	
Thickness	mm	2mm	
Hardness Shore		3mm	
		5mm	

Axle material	Colour
steel uncoated	
steel galvanised	
Niro 1.4305	

Drive data:

Chain wheel ☐

Round belt groove ☐

Single chain wheel:	Fixed drive ☐	3/8 ☐	AE-MK(a):	groove Ø _____	measure a
	steel ☐ plastic ☐	Accumulation drive ☐	1/2 ☐	MK-MK(b):	measure b
Double chain wheel:	Adjustable ☐	5/8 ☐	MK-RL(c):		measure c
	steel ☐ plastic ☐	Welded ☐	3/4 ☐		
Number of teeth _____					

Tooth belt wheel ☐

Accessories:

Poly-Chain 8M	Fixed drive ☐
	Accumulation drive ☐
	Welded ☐
	Number of teeth _____

Quantity	External Ø
Flanged wheel ☐	
Buffer Ring ☐	
Support ring ☐	
Con. Elements ☐	

Ribbed belt ☐



General

These terms and conditions apply to all legal matters between us and our clients. They are deemed accepted upon order placement. Deviating purchasing terms and conditions shall not be binding even if we do not expressly object to them.

Our contracting representatives are not authorized to modify the pre-formulated contract text or the additional verbal agreements verbally or by telephone.

All technical data set forth in the catalogue and drawings is approximate in value and non-binding.

Offers

Our offers are without obligation and non-binding. We reserve our unrestricted property rights and copyrights for all drawings, sketches, samples which are enclosed with the offers. They may not be made accessible to third parties and are to be sent back to us immediately on demand.

Dispatch

According to Incoterms 2010. Unless otherwise agreed delivery risk and cost are the recipient's responsibility in any case.

In the absence of shipping instructions from the customer, shipping will be done at our discretion in the most cost-effective manner.

Costs for packaging are calculated at cost price and used packaging returns are not accepted.

Delivery

Our delivery is done as soon as possible. The delivery period shall be extended to an appropriate extent in the event of measures within the scope of lawful industrial disputes, in particular strikes lock-outs as well as the occurrence of unforeseeable obstacles, which are beyond our control in so far as such obstacles demonstrably have a considerable influence on the delivery of the item. This also applies, if the circumstances arise with sub-contractors.

We are also not to answer for the above mentioned circumstances, if they arise during an already existing delay. The beginning and end of such obstacles are in serious cases to be notified by us to the customer. The customer is only entitled to rescission of the contract after setting an appropriate period of grace. If orders placed are withdrawn or annulled the customer is obligated to so accept and pay for any initiated production quantities produced to this date.

Call orders must be accepted by the customer no later than 6 months after order placement. We are entitled to invoice the customer even if the call has not been made.

Variations in quantities

We reserve the right to deliver an additional or under quantity of 2%, with special deliveries, 10%.

Price

Our prices are subject to change and are understood as ex-works Factory Rheineck, plus statutory value added tax as well as packaging, customs and insurance costs.

Terms of payment

Unless otherwise agreed, the settlement will be in Swiss Francs.

invoices are payable in full within 30 days of the invoice date net or within 10 days with a 2% cash discount.

A cash discount will only be granted, if all previous invoices have been settled.

If our terms are exceeded, we are entitled to charge interest at the rate which the bank charges us for our overdraft facility.

With orders above CHF 20'000.00,- one third of the order sum is payable on placing the order, one third upon readiness of ship and notification of readiness to ship to the customer and one third upon delivery. If, during the term of the contract, the buyer's financial situation deteriorates or if, in our opinion, we receive unsatisfactory information concerning the buyer which first occur following the contract termination, all payments shall be due immediately.

We shall then be entitled to demand additional securities as well as to withdraw from the contract following a reasonable time period.

We reserve the right to accept bills of exchange as payments on account. All costs arising in this regard shall be borne by the customer.

Retention of title

All delivered goods remain our property up to a complete settlement of all our claims against the customer arising out of the business relationship.

The buyer is entitled to sell the items delivered in the proper course of business as long as the customer is not in default of payment, but may not be pledged as collateral or assigned.

In the case of pledges and seizure of the goods, the customer must immediately notify us. On conclusion of the sales contract with us it cedes to us the claims accruing to it from the sale or based on other legal grounds including all ancillary rights to the full amount. The customer shall retain the right to collect the receivables as long as the customer is not in default of payment to us.



If the value of demands or collateral exceeds our total demand against products subject to claim by more than 20%, we shall be obliged to back transfer upon the customer's request.

Liability for defects

For any defects in the products supplied, including the absence of promised characteristics, we shall be liable in such a way that we will repair damaged/defective parts free-of-charge or deliver replacement. Defects shall be notified to us within one week of delivery. Parts free of defects must be sent to us upon request carriage paid. The shipping of replacement parts shall be done at the cost and risk of the customer. Any parts which we have replaced shall be our property. Claims for defects by the customer lapse in any case six months from the time of the timely notice of complaint but no earlier than the expiry of the liability period.

No liability will be accepted for supplied parts that are subject to premature wear and tear as a consequence of their material character or the way in which they are used, or for damage as a consequence of usual wear, straining, erroneous or negligent handling, unsuitable means of operation, defective construction, or as a consequence of the influence of temperature, the weather, chemical or electrical influences or as a consequence of other influences of nature. Other claims by the customer in particular claims for replacement of damages which were not incurred in the delivery itself, shall not be covered insofar as they are legally permitted.

Claims not expressly conceded in these conditions of sale and delivery, in particular claims for damages resulting from breach of impossibility, default, violation of contractual secondary obligations, wrongful act - also as far as such claims are tied up with the warranty rights of the customer - are excluded, unless we are preemptorily liable in case of gross negligence or malice.

If through our fault the delivered item cannot be used as provided for in the contract because of non-implementation or deficient implementation of proposals or consultation, whether made or provided before or after conclusion of the contract, or of contractually agreed collateral obligations – in particular instructions for the operation and maintenance of the delivery item – the provisions shall apply accordingly, all other claims of the customer being excluded.

Severance clause

In the event that individual provisions hereof should be or become invalid, the invalid provision shall be replaced by a valid substitute provision which most closely reflects the originally-intended commercial purpose. Should individual provisions of these Terms of sale and delivery be or become invalid, the validity of the other provisions shall remain unaffected.

Applicable Law and Jurisdiction

All legal relations between us the customer shall be governed by Swiss law.

The court of jurisdiction for all disputes between us and our customers is CH-9450 Altstätten. We also have the right to prosecute the customer at the responsible court of the customer's residence or any other court.

Transferability of contract rights

The customer shall not assign his contractual rights to any third party without our express permission.

PEKO ROLLEN AG
Peter Köppel
Langenhagstrasse 13
CH-9424 Rheineck